



versatile
extended color
white, clear ink option
flatbed
inkjet printer

Acuity Select HS

The Acuity Select HS flatbed inkjet printer from Fujifilm delivers all of the market leading image quality, performance and reliability benefits of the Acuity series. The Acuity Select HS has up to 6 channels offering extended color, white and clear ink options. These options further enhance productivity and add versatility for an even greater range of applications.

Acuity Select HS Features

- User controlled zoned print bed vacuum
- In line double strike white capability
- In line varnish option
- New job handling capability and throughput
- Improved image quality uniformity through print-bed mapping

		Select HS	Select HS X2
Print Technology		Piezo Drive	
Rigid Media		Maximum media size: 49.2 x 98.4 x 1.89" (1.25m x 2.5m x 5cm) Maximum print area: 49.6 x 98.8" (1.26 x 2.51m)	Maximum media size: 98.4 x 120 x 1.9" (2.5m x 3.0m x 5cm) Maximum print area: 98.8 x 120.4" (2.51 x 3.06m)
Roll Media		Roll Width: 35.4 - 86.6" (0.7 - 2.2m) Maximum print width: 86.2" (2.19m) Maximum roll weight: 110 lbs (50kg)	
Ink	Configuration	C/M/Y/K/W/V Fujifilm Uvijet KA/KI series	
	Package	2L pouch (C,M,Y,K) 1L pouch (W, V)	
Ink Type		Fujifilm Uvijet KA and KI series UV curable inks	
Print Head		Toshiba Tec CE-2 greyscale, variable drop 6pl – 42pl 2 printheads per channel	
Number of Nozzles		636 nozzles/color - single color per head	
Printing Resolution		Image quality is equivalent to 1,200dpi resolution or higher	
Connectivity		100/1000BASE-T	
Environment Temperature		64°F to 86°F (18°C to 30°C)	
Humidity		30% to 70% with no condensation	
Media Type		Targeted at rigid PVC, PETG, acrylic, foam board, With roll unit - self adhesive PVC, banner material, PET, and paper.	
RIP Recommendation		ColorGATE Production Server V. 8 or later or Caldera GrandRIP V. 9 or later	
Power Requirements		50Hz, 200 to 240 VAC, Single Phase, 16A 60Hz, 208 to 240 VAC, Single Phase, 16A Two AC power circuits	
Dimensions (W) x (D)		Printer only: 183 x 78" (4.7 x 2.0m) Printer & Roll media option: 183 x 90" (4.7 x 2.3m)	Printer only: 183 x 150" (4.7 x 3.8m) Printer & Roll media option: 183 x 162" (4.7 x 4.1m)

Mode	Select HS - 4 channel						Select HS - 6 channel					
	Std. Flatbed		X2 Flatbed		Roll-to-Roll		Std. Flatbed		X2 Flatbed		Roll-to-Roll	
	ft ² /hr	m ² /hr	ft ² /hr	m ² /hr	ft ² /hr	m ² /hr	ft ² /hr	m ² /hr	ft ² /hr	m ² /hr	ft ² /hr	m ² /hr
Express	646	60	696	64.7	466	43.3	646	60	696	64.7	466	43.3
Production Squared	-	-	-	-	-	-	498	46.3*	535	49.7*	410	38.1*
Production	404	37.5	431	40	309	28.7	-	-	-	-	-	-
Product Smooth	-	-	-	-	-	-	404	37.5*	431	40*	309	28.7
Quality Squared	337	31.3	358	33.3	272	25.3	337	31.3	358	33.3	272	25.3
Quality	285	26.5	302	28.1	229	21.3	285	26.5	302	28.1	229	21.3
Quality Density	157	14.6	166	15.4	126	11.7	157	14.6	166	15.4	126	11.7
Quality Smooth	157	14.6	166	15.4	126	11.7	157	14.6	166	15.4	126	11.7
Fine Art	227	21.1	241	22.4	183	17	227	21.1	241	22.4	183	17
Quality Layered (white) 2 layer	-	-	-	-	-	-	142	13.2	150	13.9	113	10.5
Quality Layered (white) 3 layer	-	-	-	-	-	-	94	8.7	98	9.1	74	6.9
Varnish gloss mode	-	-	-	-	-	-	73	6.78	87	8.1	-	-

*Only available in C/C/M/M/Y/K configuration