

SEPA255-DM Solar Electric Power Assembly



Features & Benefits:

- The SEPA255 solar electric power assembly features a single module ranging between 255-300 Watts mounted to our double support power bracket. Optional full sheet metal protection for the back of the panel.
- The 224 Amp hour battery assembly, consisting of two 112 amp hour batteries, is contained within a vented aluminum battery box and includes a wiring harness and control electronics. Optional keyed lock.
- There are 14 different controllers to chose for different types of applications such as dusk to dawn, dusk activated timer, and motion activation.
- The systems are built for easy installation with quick connect terminals and can be mounted to a wall, roof, or pole.
- Every system is available to produce DC or AC power depending on the needs of the device.
- Meets AASHTO wind force ratings.
- Powder coating and custom design available.
- 5 year maintenance free system, warranty up to 25 years (see warranty) and ETL Listed.



Solar Electric Power Company

1521 SE Palm Court, Stuart, FL 34994 | ph: 772-220-6615 | fax: 772-220-8616 | www.sepco-solarlighting.com



Specifications

Panel Assembly

The SEPA255 single array consists of one solar module ranging from 255 to 300 Watts which is mechanically fastened to a vented aluminum panel pan with stainless steel fasteners, optional full sheet metal backside protection, terminated in industry standard MC4 connectors. Solar array produces 20 +/- amps charge current and measures 40”L x 66”W x 2.1”D. The array has a 10 year warranty for 10% power loss and 25 year warranty for 20% power loss. The solar array has a life cycle and actual field proven life of over 30 years.

Battery Assembly

A vented aluminum box containing two 112 amp hour sealed GEL batteries, totaling 224 amp hours, which is integrally mounted and pre-wired to include a standard wire harness with simple plug in connections for the SEPCO MPPT Adaptive Lighting Control and the solar panel assembly. The low profile design contains a preformed and welded back mounting plate for easy attachment to a pole or wall. Battery assembly contains SEPCO unique “Through the Pole” rear wire routing output for no exposed wiring to provide a neat clean appearance for the finished installation.

The batteries are warranted for 5 years. Battery assembly is complete with all stainless steel mounting hardware. All metal crafting has been performed by high speed robotic presses using computer programmed instructions.

Power Bracket

An all aluminum, unique double support power bracket (5° or 45°) consists of a substantial aluminum channel affording mounting to any pole or wall. Circumference welding of strong 2-1/4” aluminum tubing in a double support arrangement to provide maximum strength for wind loading. The power bracket contains predrilled and tapped battery slide mount bolts of stainless steel and two 11/16” mounting holes for utility standard 5/8” mounting bolts. The bracket contains the unique “Through the Pole” battery wire hole for no exposed system wiring.

The SEPCO solar electric power assemblies have proven themselves as the most rugged and robust design in thousands of installations worldwide since their introduction in 1994. SEPCO systems surpass all codes, compliances, and quality controls.



Solar Electric Power Company

1521 SE Palm Court, Stuart, FL 34994 | ph: 772-220-6615 | fax: 772-220-8616 | www.sepco-solarlighting.com