

The Genuine. The Original.



Advanced Service Doors

	Non-insulated		Insulated	
	611	621	626	627 AP
Application	exterior & interior opening requiring a high-speed, high-cycle door	exterior & interior opening requiring a high-speed, high-cycle door	exterior & interior opening requiring an insulated high-speed, high-cycle door	Advanced Performance Insulated service door
Standard max width	20'0" (6096mm)	20'0" (6096mm)	20'0" (6096mm)	30' (9,144 mm)
Standard max height	20'0" (6096mm)	20'0" (6096mm)	20'0" (6096mm)	19' (5791 mm)
max size	400 sq ft	400 sq ft	400 sq ft	550 sq ft
Mounting				
Face of Wall mounting	S	S	S	S
Between jamb mounting				O
Operation				
High Cycle Direct Drive Gear Motor	S	S	S	
Manual hand crank override	S	S	S	
Chain				S
Crank				O
Electric Operator				O
Curtain				
material - galvanized steel	S	S	S	S
material - Stainless Steel	O	O	O	O
material - aluminum	O	O	O	O
Slat Profiles				
Curved	S			
Flat	O	S	S	S
Insulated			S	S
Fenestrated	O	O		
Vision lites	O	O	O	O
Finish	High performance special formulated hardness graffitti resistance powdercoat	High performance special formulated hardness graffitti resistance powdercoat	High performance special formulated hardness graffitti resistance powdercoat	Primed paint
Standard Colors	gray, tan	gray, tan	gray, tan	gray, tan, white, brown
Powder Coat available in 197 colors	O	O	O	O
Bottom bar				
Bottom bar: galvanized steel	S	S	S	O
Bottom bar: stainless steel	O	O	O	O
Bottom bar: aluminum	O	O	O	O
Weatherstripping				
Bottom Bar				S
Exterior curtain-side guide				S
Interior curtain-side guide				S
Lintel Seal				S
Windload				
Windload 20 psf	S	S	S	S
Optional High-windload package	O	O	O	O
Hood				
primed galvanized steel - painted black	S	S	S	O
primed galvanized steel - powdercoated	O	O	O	O
stainless steel	O	O	O	O
aluminum - powdercoated	O	O	O	O

Key

S = Standard

O = Optional