

The Genuine. The Original.



**Coiling Security Grilles**

**Advanced Performance Security Grilles**

	670	671	674	676
<b>Application</b>	Security grilles provide an array of attractive solutions for a spectrum of retail, commercial and industrial applications.	Security grilles provide an array of attractive solutions for a spectrum of retail, commercial and industrial applications.	Security grilles provide an array of attractive solutions for a spectrum of retail, commercial and industrial applications.	Advanced Performance high-cycle security grilles. Applications requiring security, high cycle, and low maintenance without sacrificing full visual access and air exchange.
Standard max width	30' (9144 mm)	30' (9144 mm)	24'4" (7417 mm)	<b>For more information see next page</b>
Standard max height	17'4" (5283 mm)	17'4" (5283 mm)	12'4" (3759 mm)	
<b>Mounting Application</b>				
Masonry/steel	S	S	S	
Non-masonry	S	S	S	
<b>Mounting</b>				
Face of Wall mounting	S	S	S	
Between jamb mounting	O	O	O	
<b>Operation</b>				
Manual push-up	S	S	S	
Chain hoist	O	O	O	
Manual hand crank	O	O	O	
Electric motor	O	O	O	
Electric motor with automatic	O	O		
Emergency Egress	O	O		
Emergency Egress with manual release	O	O		
<b>Grille</b>				
Straight lattice pattern standard	S	S		
Staggered brick pattern	O	O		
perforated slat			S	
<b>Curtain Material</b>				
Aluminum - Mill Finished	S			
Aluminum with polycarbonate	O			
Aluminum - Clear Anodized	O		S	
Aluminum - Bronze Anodized	O			
Galvanized Steel		S		
Stainless Steel		O		
Stainless Steel - Primed		O		
Powder Coat available in 197 colors		O	O	
Hood (galvanized, stainless steel or aluminum)	O	O	O	
Bottom Bar - tubular	S			
Bottom Bar - double angle steel		S		
Bottom Bar - clear anodized extruded aluminum center locking			S	
<b>Locking Mechanism</b>				
Slide bolt	S	S		
Cylinder lock	O	O	O	

**Key**  
 S = Standard  
 O = Optional

The Genuine. The Original.



## Advanced Service Doors

		<b>676 AP</b>
<b>Application</b>		Advanced Performance high-cycle security grilles. Applications requiring security, high cycle and low maintenance without sacrificing full visual access and air exchange.
	Standard max width	30' 4" (9246 mm)
	Standard max height	14' 4" (4369 mm)
	max size	320 sq. ft.
<b>Mounting</b>		
	Face of wall mounting	S
<b>Operation</b>		
	High cycle direct drive gear motor	S
	Manual hand crank override	S
<b>Curtain</b>		
	Galvanized steel link, galvanized steel rod, and mill aluminum spacer tube	S
	Mill aluminum link, galvanized steel rod, and mill aluminum spacer tube	O
	Clear anodized aluminum link, galvanized steel rod, and clear anodized aluminum spacer tube	O
	#4 finish stainless steel link, rod, and spacer tube	O
	#2B finish stainless steel link, rod, and spacer tube	O
<b>Slat profiles</b>		
	Powder Coat available in 197 colors	O
<b>Bottom bar</b>		
	Bottom bar: tubular extruded mill aluminum	S
	Bottom bar: stainless steel	O
	Bottom bar: galvanized steel	O
<b>Weatherstripping</b>		
	Bottom bar	S
<b>Hood</b>		
	primed galvanized steel - painted black	S
	primed galvanized steel - powder coated	O
	stainless steel	O
	aluminum - powder coated	O

### Key

S = Standard

O = Optional