

The Genuine. The Original.



Rolling Service Doors

	Non-insulated			Insulated	
	600	610	620	625	627 AP
Application	Light commercial, mini warehouse and economy projects	Heavy duty industrial	Heavy duty industrial with weatherstripping	Insulated service door	Advanced Performance Insulated service door
Standard max width	16' (4877 mm)	30' (9,144 mm)	30' (9,144 mm)	30' (9,144 mm)	30' (9,144 mm)
Standard max height	16' (4877 mm)	28' (8534 mm)	28' (8534 mm)	28' (8534 mm)	19' (5791 mm)
max size	256 sq ft	900 sq ft	900 sq ft	900 sq ft	550 sq ft
Mounting					
Face of Wall mounting	S	S	S	S	S
Between jamb mounting		O	O	O	O
Operation					
Manual push-up	S	S	S		
Chain	O	O	O	S	S
Crank		O	O	O	O
Electric Operator	O	O	O	O	O
Curtain					
material - galvanized steel	S	S	S	S	S
material - Stainless Steel		O	O	O	O
material - aluminum		O	O	O	O
Slat Profiles					
Curved		S			
Flat	S	O	S	S	S
Insulated				S	S
Ventilated		O	O		
Fenestrated		O	O		
Vision lites		O	O	O	O
Finish - primed paint	S	S	S	S	S
Standard Colors	white/white, brown/white white/brown	gray, tan, white, brown	gray, tan, white, brown	gray, tan, white, brown	gray, tan, white, brown
Powder Coat available in 197 colors		O	O	O	O
Galvanized steel bottom bar	O	O	O	O	O
Weatherstripping					
Bottom Bar	O	O	O	O	S
Exterior curtain-side guide			O	O	S
Interior curtain-side guide			O	O	S
Lintel Seal			O	O	S
Windload					
Windload 20 psf		S	S	S	S
Optional High-windload package	O	O	O	O	O
Hood					
Hood	O	S	S	S	S
Internal Hood Baffle			O	S	S
Locking Mechanism					
slide bolt	S	S	S	S	S
cylinder lock	O	O	O	O	O
Available Options					
Optional High-usage package		O	O	O	O*
Pedestrian Pass Door		O	O	O	O
Exhaust ports		O	O	O	O

* High usage package is required for high cycle and large size doors

Key

S = Standard

O = Optional