COMPACTORS

and ge

Self-Contained Compactor



\!\!\!\

- Remote Power Units with Cover
- UL Listed Relay Control Box
- Quick Disconnect with Drip Pan
- Two 3" Fire Ports
- Operator's Controls with 15' Sealite
- Oil Level Sight Gauge with Thermometer
- Double End Pick-Up
- TEFC Motors (Tri-Voltage)
- Easy closing semi-automatic slam lock door (standard)

- Two 2" x 4" x ¼" vertical tubings welded inside to the face of the container to give it greater strength and longevity (standard)
- All compactors are primed and painted in one of ten standard colors
- Two grease fittings located on each side of charge box for preventative maintenance (standard)
- Controls: push button start, dead man/hand key switch, forward-reverse selection switch, mushroom emergency stop and 80% and 100% container full light (standard and manual override)

ALL PRODUCTS ARE BUILT RUDCO TOUGH IN THE USA





Rental Program And Financing Available

www.rudco.com

COMPACTORS

Self-Contained





Self-Contained Compactor Specifications

	RT-1000	RT-1500	RT-2000	RT-3000	RP-2000	RP-3000	RP-3500	RP-4000
CHARGE BOX CAP MFG. RATING	1.0 CUBIC YARDS	1.0 CUBIC YARDS	2.0 CUBIC YARDS	2.0 CUBIC YARDS	2.0 CUBIC YARDS	2.0 CUBIC YARDS	2.0 CUBIC YARDS	2.0 CUBIC YARDS
MSWMA RATING	.74 CUBIC YARDS	.74 CUBIC YARDS	1.42 CUBIC YARDS	1.42 CUBIC YARDS	1.54 CUBIC YARDS	1.54 CUBIC YARDS	1.54 CUBIC YARDS	1.54 CUBIC YARDS
CYCLE TIME	28 SEC.	28 SEC.	30 sec.	30 SEC.	30 SEC.	30 SEC.	30 SEC.	30 SEC.
NORMAL RAM FORCE	21,400	21,400	40,231	40,231	39,900	39,900	39,900	39,900
MAXIMUM RAM FORCE	25,100	25,100	45,100	45,100	43,500	43,500	43,500	43,500
NORMAL OPERATING PRESSURE	1700	1700	1700	1700	1700	1700	1700	1700
MAX OPER. PRESSURE	2000	2000	2300	2300	2000	2000	2000	2000
CYL (BORE X STROKE X ROD)	4"X31-5/8" X 2-1/2"	4"X31"-5/8" X 2-1/2"	5"x42"x3"	5"X42"X3"	(2) 4"X31-5/8 X -1/2"	(2) 4"X31-5/8X-1/2"	(2) 4"X31-5/8X-1/2"	(2) 4"X31-5/8X-1/2"
MOTOR	5 HP	5 HP	10 HP	10 HP	10 HP	10 HP	10 HP	10 HP
PUMP SIZE	6.5 GPM	6.5 GPM	10.5 GPM	10.5 GPM	10.5 GPM	10.5 GPM	10.5 GPM	10.5 GPM
PACKER FLOOR	3/8" PLATE	3/8' PLATE	3/8" PLATE	3/8" PLATE	3/8" PLATE	3/8" PLATE	3/8" PLATE	3/8" PLATE
PACKER SIZES	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL	1/4" PLATE W/ 6" CHANNEL
RAM TOP	1/4" PLATE	1/4" PLATE	1/4" PLATE	1/4" PLATE	1/4" PLATE	1/4" PLATE	1/4" PLATE	1/4" PLATE
RAM FACE	3/8" PLATE W/ 4"X3" ANGLE	3/8" PLATE W/ 4"X3" ANGLE	3/8" PLATE W/4"x3" ANGLE					
CHARGE BOX OPENING	26" X 43"	26" X 43"	36" X 60"	40" X 60"				
DIMENSION - A	100"	100"	108"	108"	100"	100"	108"	108"
DIMENSION - B	169"	192"	223"	281"	221"	281"	281"	305"
DIMENSION - C	72"	95"	126"	186"	130"	190"	190"	214"
DIMENSION - D	70"	70"	88"	88"	84"	84"	84"	84"
DIMENSION - E	26"	26"	36"	36"	40"	40"	40"	40"
WEIGHT	4,875	7,300	8,900	10,100	9,000	10,250	10,300	10,800

AVAILABLE OPTIONS

- Guide Rail
- Doghouse W/ 30"x40" Door On Each Side
- Hopper 45° (Cellar Type) With Doors
- Thru-Wall Chute Side 40"H x 96"L W/ Door (40" x 40" Free Standing Chute)
- Thru-Wall Chute Rear 40H x 96"L With Door (40" x 40" Free Standing Chute)
- Hinged Dock Extension
- Single Phase Power Unit
- Multi Cycle Timer

- Color Pressure Gauge
- Oil Heater
- Ozone Odor Control System
- Additional Options Available

RUDCO RESERVES THE RIGHT TO REVISE, AMEND AND IMPROVE IT'S EQUIPMENT WITHOUT NOTICE



CORPORATE OFFICE: 114 E. Oak Rd. • Vineland, NJ 08360 • Ph:1.856.691.0800 • Fax: 1.856.696.0084 **MAILING ADDRESS:** P.O. Box 705 • Vineland, NJ 08362

www.rudco.com