KaVo EXPERTmatic Attachments

Superior KaVo Performance

- Powerful Performance with Patented KaVo Chuck
- Lasting Durability with Stainless Steel Heads
- Superior Ergonomics with KaVo EXPERTgrip



KaVo's Superior Performance comes standard on all EXPERTmatic attachments

Features	Benefits	
Dent resistant stainless steel heads	Durability and longer life with dent resistant heads	
Superior chuck strength of 30N	 Higher chuck strength holds the bur firmly in place and delivers precise cutting performance 	
• Smaller head size on E25L (Head Height: 14.7mm and Head Diameter: 10.2mm)	• Improved treatment efficiency and accessibility thanks to the new smaller head size	
New smoother EXPERTgrip surface	Better handling and ergonomics with EXPERTgrip	
Multi-port spray	Optimal cooling at bur-tip with multi port spray	
Spray micro-filter	• Limits clogging of the spray channels with field replaceable water filter	

Go to WWW.TRYKAYO.COM to start your free and easy trial today!



KaVo EXPERTmatic Attachments



Item	Description	Part #
EXPERTmatic E25 L (optic) EXPERTmatic E25 C (non-optic)	 Speed Increasing 1:5, Ceramic bearings, speed range up to 200,000 rpm Internal air/water coolant, Friction grip push button auto-chuck 3-port spray, EXPERTgrip, Universal "E" type connection 	E25 L - 1007.5550 E25 C - 1007.5551
EXPERTmatic E20 L (optic) EXPERTmatic E20 C (non-optic)	 Transmission 1:1, for latch type burs, speed range up to 40,000 rpm (electric motor) and 20,000 rpm (air motor) Internal air/water coolant, Push button auto chuck, 1-port spray, EXPERTgrip, Universal "E" type connection 	E20 L - 1007.5540 E20 C - 1007.5541
EXPERTmatic E15 L (optic) EXPERTmatic E15 C (non-optic)	 Reduction 5.4:1, for latch type burs, speed range up to 40,000 rpm (electric motor) and 20,000 rpm (air motor) Internal air/water coolant, Push button auto chuck, 1-port spray, EXPERTgrip, Universal "E" type connection 	E15 L - 1007.5530 E15C - 1007.5531
EXPERTmatic E10 C	 Transmission 1:1, for straight handpiece burs, speed range up to 40,000 rpm (electric motor) and 20,000 rpm (air motor) Internal air/water coolant, 1-port spray, EXPERTgrip, Universal "E" type connection 	1007.5560
EXPERTmatic E31 C	• Reduction 5.4:1, Ideal speed less than 5000 rpm, speed range up to 7,400 rpm (electric motor) and 3,700 rpm (air motor), EXPERTgrip, Universal "E" type connection	1008.4998
EXPERTmatic E61 C	 EVA, 10,000 rpm optimal drive speed (20,000 rpm max. drive speed) To be used with Intensiv files (ORTHOstrips or Proxoshapes), 36 individual locking positions Internal air/water coolant, 1-port spray, EXPERTgrip, Universal "E" type connection 	1008.4999
ELECTROtorque Plus	ELECTROtorque system with KL703 short motor with forward/reverse speed adjustment	1002.5015
QUATTROcare Plus® Maintenance System	Automatic Handpiece Maintenance and Purging System	1008.3805
E-Type Adapter	E-Type adapter for INTRAmatic Low-Speed and surgical attachments	0411.7981



KaVo QUATTROcare Plus

Protect your investment with KaVo's Automatic Handpiece Maintenance System. Prior to every sterilization, the unique cleaning and maintenance mixture of KaVo QUATTROcare Plus Spray produces highly effective cleaning foam inside the instrument. The automatic dispenser delivers the precise amount of cleaner and lubricant time after time, leading to longer handpiece life and less repair needs.

Part No. 1008.3805

Go to WWW.TRYKAVO.COM to start your free and easy trial today!

