

R140 Badge Tag

The R140 badge tag is specifically designed for tracking personnel and their interaction with tagged assets.

Features & Benefits

- ◆ Encoded Radio Transmissions at 433 MHz
- ◆ Designed for Tracking Personnel
- ◆ Clip to Clothing or Hang from a Lanyard
- ◆ Optional 2 Second Beacon Rate for Security Applications
- ◆ Low Power Consumption for Long Battery Life
- ◆ Superior Anti-Collision Technology for High Tag Densities

The R140 Badge Tag is a battery-powered RF transmitter that can be clipped onto an article of clothing or worn around the neck with a lanyard. Every tag broadcasts its unique ID and a status message at a periodic rate (pre-programmed at time of manufacturing).

R140 Badge Tags are specifically designed for tracking personnel and their interaction with tagged assets. When used with strategically-placed RF Code readers, badge tag transmissions can be mapped in real-time to track personnel

movement, entrance and exit from selected work sites or controlled areas.

R140 badge tags operate as security tags, emitting their unique identification number once every two seconds to enable continuous monitoring. Tag cases are impact resistant, splash resistant and temperature stable. Read ranges up to 1,000 feet can be obtained with optional antenna configurations. The standard tag operates with a very low duty cycle that translates to long battery life (typically > 3 years at a 2-second beacon rate).



RF Code R140 Badge Tag Specifications

OPERATION

Operating Frequency	433.92 MHz
Group Code & Tag ID Codes	> 540,000 unique IDs per Group Code
Typical Transmission Range	Up to 300 ft
Radiated Emissions	71.8 dBuV/m at 3 meters (maximum)
Modulation	ASK
Stability	Saw stabilized

ENCLOSURE

Case Length	2.15 in (54.60 mm)
Case Width	3.40 in (86.36 mm)
Case Height	0.22 in (5.58 mm)
Case Weight (with tag)	0.90 oz (25.5 g)
Construction	Injection-molded polycarbonate enclosure
Durability	Tough, impact resistant and temperature stable

ENVIRONMENTAL

Operating Temperature	-20° C to +70° C
Storage Temperature	-40° C to +80° C
Sealing	Splash resistant

POWER

Battery Type	Lithium CR2032 coin cell
Smart Tag Feature	Low battery indication
Battery Life	> 3 years *

* Battery life measured at 2-second beacon interval.



9229 Waterford Centre Blvd. ♦ Suite 500
Austin, TX 78758

Tel: 512.439.2200 ♦ Fax: 512.439.2199
sales@rfcode.com ♦ <http://www.rfcode.com>

Copyright © 2012 RF Code, Inc. All Rights Reserved. RF Code and the RF Code logo are either registered trademarks or trademarks of RF Code Incorporated in the United States and/or other countries. All other trademarks are the property of their respective owners.

01/11/2012