

fi-6130/fi-6230

Color Duplex Workgroup Scanners

Enhanced for the ultimate
in performance and reliability



- Fast, 40ppm / 80ipm scanning in monochrome and grayscale
- Exceptional 300 dpi color scanning at 30ppm / 60ipm
- Advanced paper handling technology for the ultimate in feeding reliability
- Robust 50-page Automatic Document Feeder (ADF) with enhanced hard embossed card scanning
- Comes with Kofax® VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro


QLS
SOLUTIONS
GROUP

FUJITSU

fi-6130/fi-6230

Color Duplex Workgroup Scanners

Discover a new level of front-office productivity with the fi-6130 and fi-6230 documents scanners

Enhanced with innovative features, the Fujitsu fi-6130 and fi-6230 scanners offer outstanding price/performance value in a compact footprint, conserving both space and budget. With duplex scanning performance of up to 80 images per minute in monochrome and grayscale, the fi-6130 and fi-6230 also delivers uncompromised high-resolution performance of up to 60 images per minute in color at an astounding 300 dpi. Engineered with one of the most advanced paper separation features in their class, the fi-6130 and fi-6230 are the first workgroup scanners equipped with reversing roller technology*, resulting in exceptional feeding reliability for an even wider variety of document weights. Furthermore, the automatic document feeder (ADF), capable of scanning document up to 10 feet long, is also robust enough to feed up to three hard cards continuously or an embossed card up to 1.4 mm in thickness. Additionally, the fi-6130 and fi-6230 harmoniously combines the security of Ultrasonic Double Feed Detection with the efficiency of Intelligent MultiFeed Function (iMFF) so that intentional double-feeds, such as a taped receipt or sticky note, can be manually bypassed while double-feed detection is enabled.

Fully Loaded One Box Solution

Fujitsu fi-6130 and fi-6230 workgroup scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for our Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all service programs, go to www.ImageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.

* Statement true as of March 2008



ADOBE ACROBAT 9 STANDARD



Fujitsu Computer Products of America, Inc.


<http://us.fujitsu.com/fcpa>

1250 East Arques Avenue Sunnyvale, CA 94085-4701

(800) 626-4686 (408) 746-7000 info@fcpa.fujitsu.com

Technical Specifications		
Model	fi-6130/fi-6230	
Image Sensor Type	fi-6130	Color Charge Coupled Device (CCD) x 2
	fi-6230	Color Charge Coupled Device (CCD) x 3
Light Source	White cold cathode discharge lamp	
Optical Resolution	600 dpi	
Output Resolution ¹	Color (24 bit)	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi) ²
	Grayscale (8 bit)	
	Monochrome	
Output Format	Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit	
AD Converter	1024 levels (10 bit)	
Output Mode	Dither / Error diffusion	
Scanning Speeds		
Output (Letter/A4 size) ³		
Color ⁴	200 dpi	30 ppm
	300 dpi	30 ppm
Grayscale ⁴ / Monochrome	200 dpi	40 ppm
	300 dpi	30 ppm
ADF Capacity ⁵	50 Sheets (letter/A4, 20 lb.)	
Document size	ADF minimum	2 in. x 3 in. (52mm x 74mm)
	ADF maximum	8.5 in. x 14 in. (Legal)
	Long document	8.4 in. x 122 in. (10 feet) ⁶
	Flatbed (fi-6230 only)	8.5 in. x 11.69 in. (216mm x 297mm)
ADF Feeding	Normal	11 to 56.2 lb. (41 to 210g/m ²)
Paper Weight (Thickness)	A8 sheets	34 to 56.2 lb. (127 to 210g/m ²)
	Card ⁶ (1.4mm) ⁷	Portrait and Landscape feeding ⁸
Interface	USB 2.0 / USB 1.1 (B type connector)	
Physical Specifications		
Power requirements	100 – 240 VAC, 50/60 Hz	
Power consumption	fi-6130	38W or less (Sleep: less than 6.2W)
	fi-6230	45W or less (Sleep: less than 6.2W)
Dimensions (WxDxH) ¹⁰	fi-6130	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)
	fi-6230	11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)
Weight	fi-6130	9.24 lb. (4.2 kg)
	fi-6230	19.36 lb. (8.8 kg)
Environmental compatibility ¹¹	ENERGY STAR® and RoHS	
Operating Environment	Temperature	42° to 95° F (5° to 35° C)
	Relative humidity	20% to 80% (non-condensing)
Inbox Contents	TWIN, ISIS™, USB cable, AC adapter	
Bundled Software	Adobe® Acrobat® Standard, Kofax® VRS® Professional and ScandAll Pro	
Options	Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6230)	
OS Support	Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) / Microsoft® Windows Server™ 2003 (32 bit/64 bit) / Microsoft® Windows Vista™ (32 bit/64 bit)	
Feed Detection Features	Ultrasonic Double Feed Detection Sensor	
	Intelligent Multifeed Function (Manual Bypass)	
Other Features	Embossed and Hard Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only).	
Limited Warranty	One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.ImagingService.com or call (800) 626-4686.	
Service Options	Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables: ScanAid™ kit. For full details, visit www.ImagingService.com or call (800) 626-4686.	
Part Number	fi-6130	PA03540-B055
	fi-6230	PA03540-B555

- Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
- Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).
- Actual scanning speeds are affected by data transmission and software processing times.
- JPEG compressed figures.
- Maximum capacity varies, depending upon paper weight.
- Supports ISO7810 embossed cards
- able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).
- Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)
- The scanning of documents that exceed 35 inches in length will be limited to using TWIN at 200 dpi or less.
- Excluding the ADF paper chute and stacker.
- PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).



©2009 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe and Acrobat are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft, SharePoint, Windows and Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ISIS is a registered trademark of Pixel Transistors, a division of Captiva Software Corporation. VRS is a registered trademark of Kofax Image Products, Inc. ABBYY FineReader are trademarks of ABBYY Software House. As an ENERGY STAR® Partner, Fujitsu Ltd. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a U.S. registered trademark. All other trademarks are the property of their respective owners. All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price and warranty, post-warranty and service programs. Printed in the U.S.A. Qty. 5M DS38201109

