



fi-6140/fi-6240

High Performance Color **Duplex Scanners**

The Fujitsu fi-6140 and fi-6240 scanners bring high performance and advanced features in a compact design

In addition to the fi-6140 scanner being the smallest scanner in its class, both models are able to scan an impressive 60 pages or 120 images perminute in Monochrome or Grayscale (Letter @ 200dpi) as well as 40 pages or 80 images per-minute in Color (Letter @ 300dpi). Furthermore, the Fujitsu fi-6140 and fi-6240 models are the first scanners in their class to adopt high-end "fi series" functions such as:

- Paper Protection technology: Protects valuable documents by halting the scanning process when it recognizes that a jam is about to occur.
- Intelligent MultiFeed Function (iMFF): Simplifies pre-scanning preparation and improves efficiency by ignoring documents that trigger false multi-feed alerts such as an attached receipt or sticky note.
- Intelligent Capture Correction Function (iCCF): Auto-color recognition, autosize detection, and auto de-skew correction provides dramatic efficiency by combining fast scanning with simultaneous high speed image processing.

Along with ultrasonic double-feed detection, long document scanning (up to 10 feet), dual interfaces (ultra SCSI and USB 2.0), and embossed card scanning, these scanners can continuously feed up to 3 hard cards (up to 1.4 mm thick) through the Auto Document Feeder (ADF).

Fully Loaded One Box Solution

The Fujitsu fi-6140 and fi-6240 scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for the Fujitsu Advance Exchange Program, provides peaceof-mind. For full details on the Limited Warranty and on all Fujitsu service programs, go to www.lmageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.









Technical Speci	ficati	ions				
Model			fi-6140/fi-6240			
Image Sensor Type		i-6140	Color Charge Coupled Device		CCD) x 2	
		i-6240	Color Charge Coupled Device (CCD) x 3			
Light Source			White cold cathode discharge lamp			
Optical Resolution			600 dpi			
Color (24 bit			t)	50 to 600 dpi		
Output Resolution ¹ Graysca		Grayscale (8	(adjustable by 1 dpi increments, 1200 dpi) ²			
Monochror		/lonochrom				
Output Format			Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit			
AD Converter			1024 levels (10 bit)			
Scanning Speed						
Output (Letter/A4 size) 3		re) ³	Simplex		Duplex	
Color ⁴	-	200 dpi	40 pp		80 ipm	
		300 dpi	40 ppm		80 ipm	
		200 dpi	60 ppm		120 ipm	
		300 dpi	40 pp			
ADF Capacity ⁵			50 Sheets (letter/A4, 20 lb.)			
Document size	ADF minimum			2 in. x 3 in. (52mm x 74mm)		
	ADF maximum			8.5 in. x 14 in. (Legal)		
	Flatbed (fi-6240		O only)	37		
ADF Feeding Paper Weight	Normal			11 to 56.2 lb. (41 to 210g/m²)		
	A8 sheets			34 to 56.2 lb. (127 to 210g/m²)		
		d ⁶ (1.4mm) ⁷	,			
Interface ⁹				Ultra SCSI (50m) / Hi gh Speed USB 2.0		
Physical Specif						
Power requirements (auto-switching)				100 – 240 VAC, 50/60 Hz		
Power consumption		fi-6140	42W or less (Sleep: less than 6.2W)			
		fi-6240	28 – 34 W, Energy saving mode: 12 W			
Dimensions (WxDxH) ¹⁰		fi-6140	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)			
(TADAT)		fi-6240	11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)			
Weight		fi-6140	_	9.24 lb. (4.2 kg)		
Environmental access (1)		fi-6240	19.36 lb. (8.8 kg)			
Environmental compatibili			ENERGY STAR® and RoHS			
		emperature elative humidity		42° to 95° F (5° to 35° C)		
Inbox Contents		ve numially		% to 80% (non-condensing) /AIN, ISIS™, USB cable, AC adapter		
				Adobe® Acrobat® Standard.		
Bundled Software Options				Adobe® Acrobat® Standard, Kofax® VRS® 4.x Professional and ScandAll Pro		
			_	Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6240)		
opasiio .				Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) /		
OS Support			Micro	Microsoft® Windows Server™ 2003 (32 bit/64 bit) / Microsoft® Windows Vista™ (32 bit/64 bit)		
Feed Detection Features			Pape	Ultrasonic Double Feed Detection Sensor Paper Protection Sensor Intelligent Multifeed Function		
Other Features			Pape Long Auto Sele	Ultrasonic Double Feed Detection, Intelligent Multi-Feed Function (iMFF), Paper Protection Function, Embossed Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only).		
Limited Warranty				One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.lmagingService.com or call (800) 626-4686.		
Service Options				Post-Warranty: Advance Exchange Plus; restrictions apply.		
			visit	Consumables: ScanAid™ kit. For full details, visit www.lmagingService.com or call (800) 626-4686.		
Part Number		fi-6140	PA00	PA03540-B005		
			1 0404	05 40 DE05		

- 1. Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner
- is scanning in simplex or duplex.

- 2. Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).
- 3. Actual scanning speeds are affected by data transmission and software processing times

PA03540-B505

- 4. JPEG compressed figures.
- 5. Maximum capacity varies, depending upon paper weight

fi-6240

- 6. Supports ISO7810 embossed cards
- 7. Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).
- 8. Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.)
- 9. Ultra SCSI interface cannot be used simultaneously with USB2.0 10. Excluding the ADF paper chute and stacker











http://us.fujitsu.com/fcpa 1250 East Argues Avenue Sunnyvale, CA 94085-4701 (800) 626-4686 (408) 746-7000 info@fcpa.fuiitsu.com

