

Material Safety Data Sheet

Cargo Dry Pack

Product Name: Cargo Dry Pack
Uses: For dehumidifying air in containers and packaging
Manufacturer: Desiccare, Inc. 211 Industrial Drive, Richland, MS
DOT Hazard Class: N.A.
DOT Shipping Name: N.A.

Hazardous Ingredient and Health Hazard Information:

A mixture of calcined clay of white and off-white particles with calcium chloride granules

When used in accordance with the instructions and the contents are not removed from the inner package, no masks or special equipment is required.

If handled in bulk, the following applies:

HAZCHEM CODE: 0

UN#: N/A

Class: N/A

Transport: Non hazardous

OSHA PEL (ACGIH TLV) for Crystalline Silica 1 mg/m (1 mg/m)³ 3

To sample for silica dust refer to NIOSH Analytical Method 7500 or OSHA method ID 142

Cargo Dry Pack is considered a low hazard, however, avoid ingestion and prolonged and repeated inhalation of dust. Avoid contact with skin and eyes. Wear protective mask.

Precautions When Handling Out of Package

Flammability: Non-combustible

Other Hazards: Avoid generating and inhaling dust

Ventilation: Normally, mechanical ventilation is required

Protective Equipment: Safety glasses, dust masks

Cargo Dry Pack

Page 2 of 2

MSDS-004

First Aid

Eyes: Flush eyes with water for approximately 10 minutes while holding eyelids open occasionally. Seek medical attention if irritation or soreness persists.

Inhalation: Remove from exposure area to fresh air. Seek medical attention if any symptoms persist.

Skin: First aid is normally not needed. As a precaution, brush powdered material from the skin and wash with soap and water.

Ingestion: If swallowed, as a precaution, rinse mouth with water. Do not induce vomiting, seek medical attention if any symptoms persist.

Safe Handling Procedures

Storage: Transport is not regulated. Keep product dry to avoid deterioration.

Protect containers against physical damage.

Spillage: Sweep up and wash down residue with water.

Waste Disposal: Landfill according to local, state, and federal regulations.

Fire Explosion: Non-combustible.

Extinguishing: Not applicable

For further information contact: Desiccare, Inc.

211 Industrial Drive

Richland, MS 39218

Phone: 601-932-0405

Fax: 601-932-0442

Revised 9/8/2002

Material Safety Data Sheet

Cargo Dry Pack

Product Name: Cargo Dry Pack

Uses: For dehumidifying air in containers and packaging

Manufacturer: Desiccare, Inc. 211 Industrial Drive, Richland, MS

DOT Hazard Class: N.A.

DOT Shipping Name: N.A.

Hazardous Ingredient and Health Hazard Information:

A mixture of calcined clay of white and off-white particles with calcium chloride granules

When used in accordance with the instructions and the contents are not removed from the inner package, no masks or special equipment is required.

If handled in bulk, the following applies:

HAZCHEM CODE: 0

UN#: N/A

Class: N/A

Transport: Non hazardous

OSHA PEL (ACGIH TLV) for Crystalline Silica 1 mg/m (1 mg/m)³ 3

To sample for silica dust refer to NIOSH Analytical Method 7500 or OSHA method ID 142

Cargo Dry Pack is considered a low hazard; however, avoid ingestion and prolonged and repeated inhalation of dust. Avoid contact with skin and eyes. Wear protective mask.

Precautions When Handling Out of Package

Flammability: Non-combustible

Other Hazards: Avoid generating and inhaling dust

Ventilation: Normally, mechanical ventilation is required

Protective Equipment: Safety glasses, dust masks