

# Rent **COOL AIR**

We know you have choices when selecting vendors and we'll work hard to earn your business each time you call.

Portable Air Conditioners are used for:

- Construction sites (concrete pours, masonry work, painting and finishing work)
- Offices and warehouses
- Industrial applications
- Cooling, heating, drying, dehumidifying and ventilation
- Emergency cooling and heating
- Disaster relief
- Special events



**888-324-7722**  
**Rentals@AirPacInc.com**

**The AirPac Advantage:**

- Fixed rental rates
- Fast, friendly service
- Dependable equipment

American Owned  American Made	COOLIT® Series			PORTAPAC® Series			
	COOLIT2600	COOLIT3000	COOLIT3300	PAC36	PAC60	PAC96	PAC120
<b>Cooling Capacity</b> Rating Conditions BTU/h / 1T=12,000 BTU	90°F, 60% RH 13,500/1.1T	90°F, 60% RH 28,000/2.3T	90°F, 60% RH 28,000/2.3T	90°F, 60% RH 36,000/3T	90°F, 60% RH 60,000/5T	90°F, 60% RH 96,000/8T	90°F, 60% RH 120,000/10T
<b>Control Features</b> Control Panel/Thermostat	<b>Standard:</b> Off - Fan - Cool <b>Option 1:</b> Electronic Thermostat with LCD Display <b>Option 2:</b> Electronic Programmable Thermostat with LCD Display <b>Option 3:</b> Electronic Programmable Thermostat with Internet Capability						
<b>Electrical Data</b> Voltage	115/1	208/230/1	208/230/1	208/230/1 or 208/230/3	208/230/1 or 208/230/3 or 460/480/3	208/230/3 or 460/480/3	208/230/3 or 460/480/3
Power Consumption (W) or (kW)	1,346 W	3,350 W	3,350 W	5,450 W	12.25 kW	18.0 kW	22.8 kW
Power Consumption (Amps)	11.7	16.0	16.0	41 @ 208/1 26 @ 208/3	59 @ 208/1 34 @ 208/3 18 @ 480/3	50 @ 208/3 26 @ 480/3	64 @ 208/3 32 @ 480/3
Fuse Size (Amps)	15	20	20	60 @ 208/1 35 @ 208/3	80 @ 208/1 60 @ 208/3 25 @ 480/3	70 @ 208/3 35 @ 480/3	90 @ 208/3 45 @ 480/3
Power Cord Gauge (AWG)	14	12	12	N/A	N/A	N/A	N/A
Cord Length (ft.)	6	5.5	5.5	----- Hard Wired -----			
NEMA Plug	5-15	6-20	6-20	N/A	N/A	N/A	N/A
<b>Evaporator</b> Fan Type	Centrifugal	7"x 7" DIDW	7"x 7" DIDW	12"x 9" DIDW	12"x 9" DIDW	12"x 9" DIDW	12"x 9" DIDW
Motor (HP) or (W)	120 W	1/5 HP	1/5 HP	3/4 HP	1Ø = 1 HP 3Ø = 1.5 HP	3 HP	3 HP
Max. Air Flow Low/High (CFM)	370/440	900/1,100	900/1,100	1,200	2,000	3,200	4,000
Max. Ext. Static (IWG)	0.2	0.8	0.8	1.0	1.0	1.5	1.5
Max. Duct Length Evap. (ft.)	N/A	30	30	100	100	100	100
<b>Condenser</b> Fan Type	7"x 7" DIDW	9"x 9" DIDW	9"x 9" DIDW	12"x 9" DIDW	12"x 9" DIDW	12"x 9" DIDW	12"x 9" DIDW
Motor (HP) or (W)	1/4 HP	1/2 HP	1/2 HP	1 HP	1Ø = 2 HP 3Ø = 3 HP	3 HP	5 HP
Max. Air Flow (CFM)	680	2,050	2,050	2,200	3,100	4,250	6,000
Max. Ext. Static (IWG)	0.5	0.8	0.8	1.0	1.0	1.5	1.5
Max. Duct Length Cond. (ft.)	25	50	50	50	50	50	50
Condenser Discharge	----- Integral 10" dia. Duct Flange/Clamp & Tile -----			16" dia.	16" dia.	18" dia.	20" dia.
<b>Compressor Type</b>	Hermetic rotary	----- Reciprocating -----		----- Reciprocating -----		----- Reciprocating (2) each -----	
<b>Dimensions</b> W x D x H (inches)	18-3/4 x 32-3/4 x 47-1/2	35-1/2 x 24 x 47-3/4	35-1/2 x 24 x 55	42 x 28-3/4 x 63-3/8	42 x 28-3/4 x 63-3/8	47-3/4 x 28-3/4 x 77	60-1/4 x 29-1/4 x 79-1/4
<b>Net/Ship Weight (lbs.)</b>	188/250	375/420	405/430	650/880	750/980	1,050/1,300	1,300/1,600
<b>Condensate Management</b> Tank Capacity (gal.)	----- 2 Tanks, 2.5 ea. & Internal Pump -----			----- Internal Pump -----			
<b>Max. Sound Level</b> w/ Condenser Duct (dB)	52	58	58	N/A	N/A	N/A	N/A
<b>Safety Certification</b>	----- ETL-Electrical Testing Laboratory -----						