# **Multi-Tool**

to fit 25mm exit shaft (Micro-perforating/Kiss-cutting; option1)

Stock Code: MT- 03 OPTION 1

Shaft Size: **25mm Exit Shaft**Outer Diameter: **44mm** 

#### **SETTINGS**



#### Additional Information

## Compatible on:

Fits machines with widths between 47 & 55cm

Machines with widths 47 & 49cm have no caliper settings please call for details

# **Contents of Package**

1x Male Blade Holder (MT-BH/03-25): used to hold the perforating/slitting blade whilst material is fed through

2 x Female Nylon Sleeve Holders (CP-AP-NSH-25): used to secure nylon perforating and kiss-cutting process

**1x Black Nylon Sleeve (CP-NY/SL-25):** used on light weight stocks (65-250/ 280gsm), to allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

1x Blue Nylon Sleeve (CP-NY/SL-25-B): used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

**Kiss-Cutting Blade (CK-02):** 

(44.35mm Outer Diameter **optional**) used for kisscutting applications

#### **Perforating Blades:**

17 TPI **(MPB-17/25mm)** (250/280-350 gsm) Blue Nylon Sleeve

17 TPI **(MPB-17/25mm)** (170-250/280 gsm) Black Nylon Sleeve

25 TPI **(MPB-25/25mm)** (100-170 gsm) Black Nylon Sleeve

52 TPI (**MPB-52/25mm**) (65-100 gsm) Black Nylon Sleeve

10 TPI **(MPB-10/25mm)** (optional) 12 TPI **(MPB-12/25mm)** (optional)

72 TPI (MPB-72/25mm) (optional)

## 2 x Black Gripper Bands (M-47):

used to feed and support material through device



Tech 121 (Blade Holder) Tech 272 (Nylon Sleeve Holder)