

BANTEX® DIGITAL MEDIA

PROCEDURES TO FOLLOW FOR BANTEX[®] BANNER FABRICS



BANNER PREPARATION:

- Keep Bantex[®] flexible vinyl laminated banner fabric stock <u>current</u>. The softening agent in vinyl called plasticizer naturally migrates to the print surface over time. Plasticizer will interfere with ink adhesion.
- Store Bantex[®] fabrics in a cool area away from direct heat sources. Plasticizer migration is accelerated by prolonged exposure to heat.
- Do not allow fabric to collect dust, dirt or contaminants in sheeting or preparation process.
- Wipe down fabric surface with isopropyl alcohol before decorating one-of-a-kind banners.



BANNER INK SUGGESTIONS:

• Bantex® banner material prints with all Solvent, UV Curable and Latex inkjet printers.



BANNER FABRICATION:

- Sew a fully turned hem stitching through three pieces of fabric.
- Stitches should be at least 1/2 inch (or 13 millimeters) from the raw edge.
- Use no more than six stitches per inch (or 25 millimeters). Too many stitches per inch will perforate and weaken the fabric.
- Sew rope or webbing into top or bottom of banner which allows banner to be tied down properly.
- Mount grommets every 18 inches (46 centimeters) along the edge but between stitch lines of the banner.
- Use spur-toothed, rolled rim grommets. (See Bantex[®] Banner Fabrication Guide).



- Fasten securely at all four corners and at grommet points to prevent wind flapping. Wind-whip can cause a banner to self-destruct.
- Assure banner is installed with sufficient tension to maintain a taut condition.

DISCLAIMER:

Herculite Products, Inc. cannot be responsible for poorly fabricated or installed Bantex[®] banners. It is the responsibility of the banner manufacturer to choose the proper Bantex[®] fabric for a given application and to use tested and proven fabrication and installation methods. All returns are subject to prior authorization by Herculite, and subject to a 20% restocking charge. Bantex[®] products have a shelf life of 6 months from invoice date and are guaranteed to print in that time frame. No returns will be accepted outside of this shelf life.







P.O. Box 435, Emigsville PA 17318 USA (800) 772-0036 (717) 764-1192 Fax: (717) 764-5211 WWW.HERCULITE.COM EMAIL: CUSTOMERCARE@HERCULITE.COM