

Kidde Engineered Fire Suppression System

Designed for use with 3M™ Novec™ 1230 Fire Protection Fluid



A UTC Fire & Security Company

Effective: March 2007


K-45-2080

Cylinder Valve Data Sheet

FEATURES

- For Use with UL Listed, ULC Listed and FM Approved Systems

P/N: 45-1X0000-000



TECHNICAL DATA

- Working Pressure: 360 to 609 PSIG
- Proof Pressure: 1000 PSIG
- Burst Pressure: 2000 PSIG
- Temperature Range: 0°F to 130°F (-18°C to 54°C)

MATERIALS

- Valve Body: Brass
- Piston: Brass
- Finish: Natural
- Seat: Rubber

P/N	Valve Size	A	B	C	D	E	F
45-140000-000	1-1/2 in.	7.63 in. (194 mm)	4.83 in. (123 mm)	5.22 in. (133 mm)	754-900 PSI (52-62 bar)	242461	9.9 lb. (4.5 kg)
45-150000-000	2 in.	8.80 in. (224 mm)	5.32 in. (135 mm)	6.28 in. (159 mm)	798-972 PSI (55-67 bar)	264925	15 lb. (6.8 kg)

Kidde is a registered trademark of Kidde-Fenwal, Inc.
3M and Novec are trademarks of 3M.
All other trademarks are property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.
If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, INC., Ashland, MA 01721. Telephone: (508) 881-2000.

Kidde Fire Systems
A UTC Fire & Security Company
400 Main Street
Ashland, MA 01721
Ph: 508.881.2000
Fax: 508.881.8920
www.kiddefiresystems.com