

Supervisory Pressure Switch

3-Inch Valve Data Sheet

(Manufactured Prior to May 1, 2013)



Effective: July 2013
K-90-9048

P/N 06-118263-001

FEATURES

- Both Normally Open and Normally Closed Configuration with One Unit
- UL Listed and FM Approved
- CRUUS Recognized Component (US and Canada)
- For Use on 3-inch Valve Cylinders Manufactured Prior to May 1, 2013 Only

DESCRIPTION

The cylinder supervisory pressure switch is intended to detect a fall in pressure in the FM-200® cylinder. The cylinder supervisory pressure switch can be wired for either normally open or normally closed operation, depending on installation requirements. This cylinder supervisory pressure switch can be installed on 3-inch valve cylinders manufactured prior to May 1, 2013. For 3-inc valve cylinders manufactured after May 1, 2013, use Supervisory Pressure Switch P/N: 06-118262-001.


OPERATION

When the pressure in the FM-200 container drops from the standard charge pressure of 360 PSI (25 bar) to below 305 PSI (21 bar) the switch operates. If wired in the NC (open-under-pressure) configuration the resulting pressure drop will cause the contacts to close. When connected to a monitored circuit of a suppression control panel the switching will result in an alarm or trouble condition.

Note: If the temperature of the container contents drop to a temperature of 32°F (0°C) or below, the pressure in the container will be equal to or less than 305 PSI (21 bar) and the switch will operate. However, the minimum operating temperature of the system is 32°F (0°C).

INSTALLATION

The supervisory pressure switch can be installed on a fully charged container, without loss of pressure, provided the unit is handled with care and only by trained service personnel. Remove the protective plug in the pressure port fitting by holding the fitting with an 5/8" open-end wrench and removing the plug with another wrench. Apply Permacel® #412D Teflon® tape to the male switch threads and while maintaining the wrench on the fitting install the switch. Tighten using a 1-1/16" open-end wrench. Leak check using a leak detector or bubbling solution. Secure switch body with wrench when connecting electrical conduit. Isolate the assembly from shock, vibration and areas subject to wide-ranging or rapid temperature fluctuations. Disconnect all supply circuits before wiring the supervisory switch.



ORDERING INFORMATION

The cylinder supervisory pressure switch offers combined normally opened and normally closed functionally. The part number for ordering the cylinder supervisory pressure switch is 06-118263-001.

SPECIFICATIONS

Setting:	305 PSI (21 bar) on falling pressure
Electrical rating:	5 Amps, 250 Vac
Wire color coding:	Blue = Normally Open Black = Normally Closed Violet = Common
Operating temperature range:	32 to 130°F (0 to 54°C)
Pressure connection:	0.125-27" NPT male connector
Wetted materials:	EPR, Brass Copper
Lead length:	36 in. +/- 2 in. (914 mm +/- 50 mm)

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.
If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, INC., Ashland, MA 01721. Telephone: (508) 881-2000.

Kidde Fire Systems
400 Main Street
Ashland, MA 01721
Ph: 508.881.2000
Fax: 508.881.8920
www.kiddefiresystems.com