



- HOSEBED CAPACITIES
- ① 300' OF 1.75" HOSE
 - ② 400' OF 2.50" HOSE
 - ③ 1000' OF 4.00" HOSE

ALUMINUM BODY

MAXIMUM O.A.L. 418.00"

SIDE ROLL & FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. INSTA-CHAIN AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
2. ALUMINUM TREADPLATE EXTERIOR REAR WALL OF CAB
3. PIERCE LOGO MUDFLAPS FRONT AND REAR
4. BATTERY CHARGE INDICATOR LOCATED NEAR D.S. SEAT RISER WITH BRACKET
5. MOUNTING FOR HURST HYDRAULIC TOOLS LOCATED IN THE BUMPER
6. TWO ADDITIONAL POLY TRAYS SHIPPED LOOSE
7. BATTERY CHARGER & COMPRESSOR LOCATED BEHIND DRIVER'S SEAT
8. STAINLESS STEEL FENDER CROWNS FRONT AND REAR
9. ONE DUPLEX RECEPTACLE LOCATED IN EMS COMPARTMENT
10. 5/STL PROTECTIVE GUARD FOR PUMP HOUSE ENCLOSURE ROLL-UP DOORS

REV	DATE	BY	CH	VELOCITY
1	14DEC15	DDO	J60	CHASSIS DATA
2	13OCT15	DDO	J60	MAKE
3	13JUL15	DDO	J60	PIERCE
4	20MAY15	DDO	J60	MODEL
5	02APR15	DDO	KBO	

	MANUFACTURING INC.		JOB NO.	28804
			SCALE	DATE
TITLE 1500-D-520P, 500G WATER W/20G FOAM CELL; 174" HDRP (2) XLAYS; ZICO H-LAS LDDR RACK; GENERATOR; DELUGE		DRAWN BY		DDO
		CHECKED BY		KBO
FOR GRIMES FIRE DEPARTMENT GRIMES, IOWA		SHEET SIZE		SHEET NO.
		D		1 OF 1
DWG NO. 28804AD-SH1				