



COMMERCIAL PUMPER & TANKER

Pierce® Commercial Pumper

Pierce's Commercial Pumper is the total package. Standard features include an aluminum body with high side compartments on each side, all-LED lighting (exterior, clearance and perimeter), roll-up doors with LED strip lighting, enclosed ladder storage, wrap-around tail lights and a full width hose bed. Its 1250 GPM Hale pump is in a 34" pumphouse featuring easy-access low height speedlays with removable trays and a full sized cargo area above. In addition, our Commercial Pumper has larger over-wheel compartments/rub rails as well as PS upper compartments that are a full 13" deep. The Freightliner M2-106 chassis also includes an exclusive 5 year/100,000 mile warranty.

BASE MODEL STOCK COMMERCIAL UNITS

- 1000 gallon, Freightliner FLM2 106 2DR Side Control
- 1000 gallon, Freightliner FLM2 106 2DR Top Mount
- 1000 gallon, Freightliner FLM2 106 4DR Side Control
- 1000 gallon, Freightliner FLM2 106 4DR Top Mount

STANDARD CHASSIS FEATURES

- Air ride driver, fixed officer seat - two (2) door chassis
- Air driver, SCBA officer & three (3) crew cab SCBA seats - four (4) door chassis
- SCBA air bottle brackets in seats - four (4) door chassis only
- 360 HP ISB Cummins engine with exhaust brake
- EVS 3000 5-speed automatic transmission
- 275 amp alternator with battery jumper studs
- 36,000 lb. GVWR two (2) door chassis (12,000 lb. FAWR & 24,000 lb. RAWR)
- 38,000 lb. GVWR four (4) door chassis (12,000 lb. FAWR & 26,000 lb. RAWR)
- West Coast bright heated & remote mirrors with convex
- Tilt & telescoping steering
- Air conditioning
- 50 gallon fuel tank
- Exclusive 5 year/100,000 mile chassis warranty

STANDARD BODY FEATURES

- 152" full-height compartments on driver side & passenger side
- Aluminum body with spatter painted interior finish
- Full height rear compartment, interior open to side compartments
- Anodized satin finish aluminum Amdor roll-up doors
- Hosebed access ladder with rear tailboard
- Brushed aluminum hosebed side walls with NFPA hose restraints
- Stainless steel fender crowns with removable fender liners
- Four (4) SCBA air bottle compartments, two (2) each side
- 1000 gallon polypropylene water tank with 1.5" tank refill
- One (1) adjustable hosebed divider
- 34" pumphouse, 45" total with speedlays
- Hale 1250 GPM pump
- Akron valves
- Electronic pressure governor
- Two (2) 2.50" discharge outlets (driver side), one (1) 2.50" outlet (passenger side) & one (1) rear 2.50" discharge outlet
- Two (2) 1.75" speedlays with 2.00" piping
- 3.00" deluge riser
- Color coded tags
- Foam system compatible with a 30 gallon integral foam cell
- Aluminum pumphouse (unpainted) with black non-glare pump panels
- Stainless steel, brass & flex hose for all plumbing
- Whelen LED NFPA lighting package
- Pierce #90 red paint
- Standard Pierce body & paint warranties
- 10 year piping warranty (includes stainless steel piping, brass fittings & valves)



Pierce® Commercial Tanker

The Pierce Commercial Tanker is loaded with the most popular features. Standard features of both the single axle 2100 gallon and the tandem axle 3000 gallon version include a painted poly water tank with a hose bed and section of poly hose bed grating, an aluminum body, roll-up doors with LED lighting and all-LED lighting (exterior, clearance and perimeter). The 500 GPM Hale pump is mounted in a 28" pumphouse and allows pump in motion capability. The Freightliner M2-106 chassis also includes an exclusive 5 year/100,000 mile warranty.

BASE MODEL STOCK COMMERCIAL UNITS

- 2100 gallon, Freightliner FLM2 106, Single Axle, 500 GPM w/PTO
- 3000 gallon, Freightliner FLM2 106, Tandem Axle, 500 GPM w/PTO
- 3000 gallon, Freightliner FLM2 106, Tandem Axle, 1000 GPM Midship Pump

STANDARD CHASSIS FEATURES

- Air ride driver seat & fixed officer seat
- 350 HP Cummins ISL engine with exhaust brake, 3000 gallon tandem
- 360 HP Cummins ISB engine with exhaust brake, 2100 gallon single
- EVS 3000 automatic transmission
- 275 amp alternator with battery jumper studs
- 45,600 lb. GVWR - 2100 gallon tank (14,600 lb. FAWR & 31,000 lb. RAWR)
- 54,600 lb. GVWR - 3000 gallon tank (14,600 lb. FAWR & 40,000 lb. tandem RAWR)
- West Coast bright heated & remote mirrors with convex
- Tilt & telescoping steering
- Air conditioning
- 50 gallon steel fuel tank
- Exclusive 5 year/100,000 mile chassis warranty

STANDARD BODY FEATURES

- Wet Side painted polypropylene water tank
- Compartments ahead & behind rear axle(s) with spatter painted interior finish
- Anodized stain finish aluminum Amdor roll-up doors
- Hard suction storage integral to compartments on 3000 gallon tandem
- Tailboard with hosebed access ladder & NFPA hose restraints
- Stainless fender crowns with removable fender liners
- 500 GPM Hale PTO pump (set for pump in motion)
- Akron valves
- Electronic pressure governor
- Two (2) 2.50" discharge outlets, one (1) driver side & one (1) passenger side
- Two (2) 1.50" crosslays with 2.00" piping
- One (1) 2.00" tank refill line
- 28" pumphouse
- Aluminum pumphouse (unpainted) with black non-glare pump panels
- Stainless steel, brass & flex hose for all plumbing
- Foam system compatible with a 30 gallon integral foam cell
- One (1) 2.50" direct tank fill at rear
- Rear 10" tank dump with manual valve & swivel chute
- Color coded tags
- Whelen LED NFPA lighting package
- Scene lights at rear
- Pierce #90 red paint
- Standard Pierce body & paint warranties
- 10 year piping warranty (includes stainless steel piping, brass fittings & valves)

