

# PLATFORM SPECIFICATIONS\*

	Custom Chassis Choices	Ladder Reach	Payload Capacity	Flow Capacity	Tank	Wind & Ice Ratings	Basket	Stabilizers	Pump Range	PUC Availability	Hosebed Capacity	Body Support Substructure	Structural Ladder Warranty	Body Warranty
<b>85' Platform</b>	Arrow XT™, Velocity®, Dash® CF & Quantum®	85' Vertical, 78'1" Horizontal	1000 lb	2000 gpm	Up to 500 gallons	Up to 20 mph winds & ¼" of ice	16 or 22 sq ft	2 sets of H-style: front and rear	Waterous, Hale, Darley Midship or PTO	Yes	1000' of 5" hose	Pierce exclusive underslung steel body support features a neoprene elastomer isolated mount system	20 years	10 years
<b>95' Mid-Mount Platform</b>	Arrow XT™, Velocity® & Quantum®	95' Vertical, 88' Horizontal	1000 lb	2000 gpm	Up to 300 gallons	Up to 50 mph winds & ¼" of ice	16 or 22 sq ft	2 sets of H-style: front and rear	Waterous or Hale	No	1000' of 5" hose	Pierce exclusive underslung steel body support features a neoprene elastomer isolated mount system	20 years	10 years
<b>100' Aluminum Platform</b>	Arrow XT™, Velocity®, Dash® CF & Quantum®	100' Vertical, 92' Horizontal	1000 lb	2000 gpm	Up to 500 gallons	Up to 35 mph winds & ¼" of ice	19.25 sq ft	2 sets of H-style: front and rear	Waterous, Hale, Darley Midship or PTO	Yes	1000' of 5" hose	Pierce exclusive underslung steel body support features a neoprene elastomer isolated mount system	20 years	10 years
<b>100' Steel Platform</b>	Arrow XT™, Velocity®, Dash® CF & Quantum®	100' Vertical, 93' Horizontal	1000 lb	Up to 3000 gpm	Up to 500 gallons	Up to 50 mph winds & ¼" of ice	18 or 22 sq ft	2 sets of H-style: front and rear	Waterous, Hale, Darley Midship or PTO	Yes	1000' of 5" hose	Pierce exclusive underslung steel body support features a neoprene elastomer isolated mount system	20 years	10 years

\*Chart is for comparison purposes only. See your Pierce representative for more information about the wide range of specifications available on each model.



[piercemfg.com](http://piercemfg.com)