

The Experts in Turbomachinery





Preliminary Design of Multistage Axial Compressor and Turbines

AXIAL™


Perform meanline design optimization for single-stage and multistage axial fans, compressors, turbines and pumps with AXIAL[™] Computer-Aided Engineering (CAE) software from Concepts NREC. AXIAL supports design-point and off-design analysis for subsonic and supersonic designs through advanced pressure-based formulation. Other AXIAL abilities include:


- Estimation of hub and tip flow parameters
- Evaluation of compressor stall and choking conditions for both compressors and turbines
- Design analysis of multiple choked and stalled components, along with mass flow, pressure ratio, and power
- Setup of an arbitrary sequence of stage elements (rotor, stator, duct, IGV, EGV, etc.)

Loss Modeling

AXIAL's state-of-the-art loss modeling system allows for the independent selection of loss models by blade row and loss split by loss component (i.e., profile, secondary flow, partial admission, wetness losses, and more). Industrystandard loss models are included for turbines and compressors.

- Ainley-Mathieson (turbine)
- Dunham-Came (turbine)
- Kacker-Okapuu (turbine)
- Moustapha-Kacker (turbine)
- Koch & Smith (compressor)
- Wright & Miller (compressor)





Users may view and edit the selected design parameters, including parameter distributions, directly in the plots using the interactive graphical editing of input data.

Real Fluid Thermodynamics

Real Fluid thermodynamics are integral to AXIAL, which includes built-in support for perfect and semiperfect fluid properties. Real Fluid Properties are provided through several different fluid databases, including D.B. Robinson Real Fluid Properties, NIST, and ASME Steam. AXIAL also supports condensed gases, user-modifiable fluid properties, and the barotropic fluid thermodynamic model.

User-Friendly Features

AXIAL includes a flexible, user-friendly interface and built-in performance mapping. Context-sensitive help is included for each parameter in each table cell.

HTML help is also available.

Graphical and Tabular View of Results

AXIAL utilizes integrated performance map plotting. Users can view blade angles and velocity triangles at the rotor inlet and exit, as well as view results in a flexible spreadsheet-like table view. Tables are customizable through separate filters, with the user able to create any number of filters, select what to display, and customize the labels as well.



Axial blade row designed with AXIAL.

OLE Automation Support

Users can control AXIAL from an external program by means of Object Linking and Embedding (OLE) automation, which supports the full control of data entry, program execution, and result retrieval. External programs can be written in Visual Basic[®], Visual C++[®], FORTRAN, Python[®] or other languages that support the Microsoft[®] OLE standard.

Direct Integration with AxCent

AxCent files can be started from within AXIAL, with the initial geometry and flow parameters transferred automatically to AxCent for blade shaping/stacking, blade-to-blade analysis, throughflow analysis, and further transfer to CFD and FEA programs. The user can also update the AXIAL solution from AxCent, transferring the more complete geometry from AxCent back to the meanline model.

	Ra	idial	~ `		Ax	ial			
Concepts NREC's Agile Engineering Desig	n System®	Carlo Carlo	Sec. Sec.	County I	Constrations	Lana and	Pranto -	1. Banda Banda	
CAE Preliminary Design									
Meanline Approach	AXIAL~					\checkmark			\checkmark
Meanline Approach	COMPAL [®]	\checkmark							
Meanline Approach	FANPAL"		\checkmark				\checkmark		
Meanline Approach	PUMPAL®			\checkmark				\checkmark	
Meanline Approach	RITAL"				\checkmark				
CAE Detailed Design									
3D Geometric Design	AxCent [®]	\checkmark	\checkmark						
CFD Option for AxCent	FINE"/Turbo"*	\checkmark	\checkmark						
Pre- & Post-Processor for AxCent	pbPost"	\checkmark	\checkmark						
FEA Option for AxCent	Pushbutton FEA**	\checkmark	\checkmark						
CAE Specialized Design Software									
Gas Turbine Blade Cooling	CTAADS"								\checkmark
Optimization	TurboOPT II*	\checkmark	\checkmark						
Rotor Dynamics	Dyrobes®	\checkmark	\checkmark						
Gas Turbine Cycle Analysis	GasTurb®	\checkmark				\checkmark			\checkmark
CAM Toolpaths									
Base Platform	MAX-PAC*	\checkmark	\checkmark						
Flank Milling Option	MAX-5"	\checkmark	\checkmark						
Point Milling Option	MAX-AB"	\checkmark	\checkmark						
Closed Impeller Option	MAX-SI"	\checkmark	\checkmark						
Single Blade Option	MAX-SB"	\checkmark	\checkmark						
3+2 Roughing Option	3+2 Roughing	\checkmark	\checkmark						



CORPORATE HEADQUARTERS

217 Billings Farm Road White River Junction, VT 05001-9486 USA Phone (802) 296-2321 • Fax (802) 296-2325 E-mail: sales@ConceptsNREC.com Web: www.ConceptsNREC.com

Agile Engineering Design System, AxCent, AXIAL, COMPAL, FANPAL, MAX-PAC, PUMPAL, Pushbutton FEA, RITAL, and TurboOPT II are registered trademarks or trademarks of Concepts NREC, LLC. Other company, product or service names, including FINE/Turbo, may be trademarks of their respective owners.

*Offered in partnership with NUMECA International® as part of the FINE/Agile" integrated suite.