

Demarcation Enclosure



Features & Benefits

- UV and weather resistant copolymer impact polypropylene material
- Designed to accommodate the Entry Series
- Self-latching, hinged cover design allows for easy access and no loose parts
- 3-way security (dual lid snaps, metal female F-port post, security hole for lock or zip-tie)
- Ergonomically designed internal mounting bosses allow for proper cable bend radius and any number of mounting configurations
- Individual, self-sealing cable entrance ports prevent insect ingress
- Custom logo (optional)

- **BABA compliant options available**



Overview

PPC's Demarcation Enclosure, designed around the Entry Series, provides a secure environment for protecting and terminating any combination of drop components and coaxial cables. The enclosure is constructed of a copolymer impact polypropylene, which is durable and sturdy yet flexible. The 11 coaxial cable ports on the bottom of the enclosure allow for a clean and easy installation. The internal mounting design allows for perfect Entry Series installations as well as any number of other passive or active installations. All mounting tabs are the same height and spaced in $\frac{1}{2}$ " increments in accordance with SCTE requirements.



Demarcation Enclosure



Technical Data

Specification	Value
UV Resistance	ASTM G26-93
Salt Fog	ASTM B117-90
Chemical Resistance	100°F and 95% RH Resists chipping and/or cracking when subjected to household chemicals
Material	Copolymer Impact Polypropylene
Dimensions (W x H x D)	11.1 in x 10.5 in x 4.6 in
Cable Entrances # x Size - Input/Output	11 x 0.635"
Cable Entrances # x Size - Ground Wire	1 x 0.310"
Cover Latching	Molded Snap Fingers, "F" Termination and security hole for lock or zip-tie

Ordering Information

Part Number	Description
EVOHB1094xx	Demarcation Enclosure (11.1" x 10.5" x 4.6")

● = BABA Compliant Product

