

Demarcation Enclosure



Features & Benefits

- Weather-resistant thermoplastic housing
- Removable 7"x4" section for covering unsightly installations
- Open-ended cable ports for easier and faster installations
- Ergonomically designed internal mounting boss layout
- Custom logo (optional)
- **BABA compliant options available**



Overview

PPC's HB1094RC74xx demarcation enclosure provides a secure compartment for terminating coaxial cables and mounting any combination of drop components. The enclosure's removable hinged lid has a section that allows for the display of your company's logo. The enclosure can be safeguarded three different ways: two side snap latches, zip-tie/pad lock or locking F-terminator. The internal mounting arrangement allows for a standardized method of installing coax drop components. All mounts are the same height and spaced in 1/2" increments per SCTE requirements. To help cover unsightly cable portals and/or components on the side of a home, the back of the enclosure incorporates an 7"x4" section that can easily be removed via a pull-tab. The open-ended, self-sealing, cable and conduit ports at the bottom of the box allow components to be assembled outside of the enclosure making for quicker installations.



Demarcation Enclosure



Technical Data

Specification	Value
UV Resistance	UL 94V-0 (indoor) and UL 94-5VA (outdoor), flame retardant PBT/PC blend thermoplastic
Salt Fog	UL1863
Chemical Resistance	30 Days at 100°F and 95% RH Resists chipping and/or cracking when subjected to household chemicals
Material	Copolymer Impact Polypropylene
Dimensions (W x H x D)	11.1 in x 10.5 in x 4.6 in

Ordering Information

Part Number	Description
HB1094RC74xx	Demarcation Enclosure (11.1" x 10.5" x 4.6")

● = BABA Compliant Product

