



# Fleetline Passenger Car Motor Oil



**Fleetline Passenger Car Motor Oils** are API licensed SN, Resource Conserving motor oils that are engineered to prevent sludge and varnish buildups. The base oils and additive packages are also specially selected to provide excellent protection against viscosity and thermal breakdown. Fleetline SAE 5W-20 and 5W-30 are synthetic blend motor oils.

**Fleetline Passenger Car Motor Oils** are formulated for turbocharged, supercharged, and naturally aspirated gasoline, gasohol (up to E85), propane, and natural gas engines. These quality oils meet or exceed the following requirements and specifications:

- Passenger cars, light-duty trucks, vans and SUVs, specifying API service SN or ILSAC rating GF-5
- Vehicles specifying previous API service categories SM, SL, SJ, SH, SG, SF or previous ratings GF-4, GF-3, GF-2 or GF-1.
- Ford WSS-M2C153-H, WSS-M2C 930-A, and WSS-M2C945-A (SAE 5W-20)
- Ford WSS-M2C 929-A and WSS-M2C946-A(SAE 5W-30)
- GM 6094M (All Grades)
- Chrysler MS-6395 (SAE 5W-20 & 5W-30)

Always refer to the vehicle's manual regarding correct viscosity grade and performance level requirements.

### Typical Analysis

Test Description	ASTM Method	SAE 5W-20	SAE 5W-30	SAE 10W-30
API Service Category	J 183	SN	SN	SN
Resource Conserving	-	Yes	Yes	Yes
ILSAC Specification	-	GF-5	GF-5	GF-5
Specific Gravity 15.6°C (60°F)	D 287	0.857	0.860	0.866
Viscosity, Kinematic, cSt @ 40°C (104°F)	D 445	51.5	60.2	69.5
Viscosity, Kinematic, cSt @ 100°C (212°F)	D 445	8.77	10.12	10.6
Viscosity Index	D 2270	153	155	140
CCS Viscosity, cP @ -30°C @ -25°C	D 5293	6230 -	6320 -	- 6300
Flash Point (Cleveland Open Cup,) °C (°F)	D 92	215° (419°)	215° (419°)	234° (453°)
Pour Point, °C (°F)	D 97	-28° (-18°)	-38° (-36°)	-36° (-33°)

Revised 7/2015

Note: Typical Analysis data is representative of average values. Minor variations which do not affect performance may occur.



## DENNIS K. BURKE INC.

THE EMISSIONS EXPERTS