

10B Timber Lane, Marlboro, NJ 07746 • (732) 780-5300 • FAX: (732) 294-0001 • www.tandcplastics.com

Sediment Interceptor Tank Dimensions & Fittings Data

Sediment Interceptor Model #	Tank Cap. Gallons	No. of Sinks to be Installed	I.D.* Dia. x Ht.	Wall Thickness	Standard inlet & outlet Conn. Sizes	Standard Fitting Connections	Approx. Typical Fitting Centerline Heights	
SI-5/HDPE	5	1	11" x 14"	3/16″	1-1/2" or 2"	Threads	4	81⁄2″
SI-15	15	1 - 4	18″ x 15″	3/16″	1-1/2" or 2"	Threads	5	10″
SI-30	30	1 - 8	18″ x 29″	3/16″	3″	Threads	8	20″
SI-55	55	1 - 12	22″ x 36″	3/16″	4″	Threads	8	26″
SI-100	100		28″ x 42″	1⁄4″	4″	Threads	12	32″

*O.D. tank dimensions are available upon request.

 \diamond Ask for drawing on this tank.

NOTE: 3" and smaller tank fittings are male or female IPS threads (standard) or plain-end pipe (for M/J fittings only). 4" is male threads or plain-end pipe (for M/J fittings only).

Flanged (150 lb. pattern) connections are available on 4" and smaller connections, at additional cost.