

# GPS Tank Liner 30, 40, 60, 80 mil

## Product Description

GPS Tank Liner is a heavy duty containment liner that excels in both puncture strength and elongation. Their unmatched flexibility and durability make GPS Tank Liner a solid solution for custom containment.

Made in the USA, this liner uses the highest quality materials for leak-proof performance. Our tank liners are fabricated into large single pieces that expedite deployment and requires NO SEAMING on the job site. It's available in the industry's most popular sizes or can be fabricated to any custom size.

## Applications

- ✓ Reserve Pits
- ✓ Frac Pits
- ✓ Retention Ponds
- ✓ Fresh Water Pits
- ✓ Flowback Pits
- ✓ Secondary Containment
- ✓ Aboveground Storage Tanks



# GPS Tank Liner 30, 40, 60, 80 mil

Manufactured In:



**ISO 9001:2008**  
CERTIFIED MANAGEMENT SYSTEM

PROPERTIES	TEST METHOD	MINIMUM AVERAGE VALUES			
		30 (0.75)	40 (1.00)	60 (1.50)	80 (2.00)
THICKNESS, MIL (MM)	ASTM D5199	27 (0.68)	36 (0.91)	54 (1.37)	72 (1.83)
TENSILE PROPERTIES (AVG. EACH DIRECTION)	ASTM D6693, TYPE IV				
STRENGTH AT BREAK, LBS. (N)		1620 (721)	197 (876)	230 (1023)	266 (1183)
ELONGATION AT BREAK (%)		1200	1145	1090	1035
TEAR RESISTANCE, LBS. (N)	ASTM D1004	18 (80)	25 (111)	30 (133)	35 (155)
PUNCTURE RESISTANCE, LBS. (N)	ASTM D4833	55 (244)	70 (311)	90 (400)	105 (467)
STANDARD ROLL DIMENSIONS					
ROLL LENGTH, FT. (M)		1210 (368.8)	910 (277.3)	600 (182.8)	405 (123.4)
ROLL WIDTH, FT. (M)		21.5 (6.553)	21.5 (6.553)	21.5 (6.553)	21.5 (6.553)
ROLL AREA, FT. <sup>2</sup> F		26,015 (2416.82)	20,020 (1817)	13,200 (1197.8)	8910 (808.6)

This data is provided for informational purposes only. Global Plastic Sheeting makes no warranties as to the suitability or the fitness for a specific use or merchantability of products referred to, no guarantee of satisfactory results upon contained information or recommendations, and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with Global Plastic Sheeting for current updates.



6020 Progressive Avenue, STE 300, Vista, CA 92154

Toll Free: 866-597-9298 760-597-9298

Fax: 760-597-9574

Email: [sales@globalplasticsheeting.com](mailto:sales@globalplasticsheeting.com)  
[www.globalplasticsheeting.com](http://www.globalplasticsheeting.com)