

MOLDED DOOR SIZE AND PROFILE OPTIONS

6'8" and 7'0" Doors	1'0"	1'2"	1'3"	1'4"	1'6"	1'8"	1'10"	2'0"	2'2"	2'4"	2'6"	2'8"	2'10"	3'0"	Sticking Profile	ProCore®	Bifolds
ATHERTON® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
ATHERTON 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
ARLINGTON 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	B	X	X
ARLINGTON 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	B	X	X
AVALON® 6'8" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
AVALON 7'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
BOSTONIAN® 6'8" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
BOSTONIAN 7'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
BRISTOL 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
BRISTOL 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
CAMBRIDGE 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CAMBRIDGE 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CAMDEN® 6'8" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
CAMDEN 7'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
COLONIAL 6'8" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
COLONIAL 7'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CONTINENTAL™ 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CONTINENTAL 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CRAFTSMAN III® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	TBD	X	X
CRAFTSMAN III 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	TBD	X	X
IMPRESSION™ MIRROR Arlington 6'8" Smooth	–	–	–	–	–	–	–	X	–	X	X	X	–	X	B	–	–
IMPRESSION™ MIRROR Colonial 6'8" Textured	–	–	–	–	–	–	–	X	–	X	X	X	–	X	O	–	–
IMPRESSION MIRROR Bostonian 6'8" Textured	–	–	–	–	–	–	–	X	–	X	X	X	–	X	MCB	–	–
PRINCETON 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
PRINCETON 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
PROVINCIAL® 6'8" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
PROVINCIAL 7'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
ROCKPORT 6'8" Smooth	–	–	–	–	–	–	–	X	X	X	X	X	X	X	MCB	X	X
ROCKPORT 7'0" Smooth	–	–	–	–	–	–	–	X	X	X	X	X	X	X	MCB	X	X
SANTA FE 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
SANTA FE 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
STANFORD® 6'8" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
STANFORD 7'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
8'0" Doors	1'0"	1'2"	1'3"	1'4"	1'6"	1'8"	1'10"	2'0"	2'2"	2'4"	2'6"	2'8"	2'10"	3'0"	Sticking Profile	ProCore®	Bifolds
ARLINGTON 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	B	X	X
ATHERTON 8'0" Smooth	–	–	–	–	–	–	X	X	X	X	X	X	X	X	O	X	X
BOSTONIAN 8'0" Textured	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
BRISTOL 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
CAMBRIDGE 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
COLONIAL 8'0" Textured	–	–	–	–	X	X	X	X	X	X	X	X	–	X	O	X	X
CONTINENTAL 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
PRINCETON 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MCB	X	X
ROCKPORT 8'0" Smooth	–	–	–	–	–	–	–	–	–	–	–	–	–	X	MCB	X	–
SANTA FE 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X


Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

Please check your local distributor for availability of 7'0" and 8'0" doors in your area.

For more detailed product specifications, please check out our JELD-WEN product line at www.jeld-wen.com.


6'8" AND 7'0" DOORS

CAMBRIDGE



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-9/16"	3-7/32" (1'6") 4-7/32" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	13-11/16"	4-1/8" (1'10") 5-1/8" (2'0")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	17-11/16"	4-1/8" (2'2") 5-1/8" (2'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-1/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21-11/16"	5-1/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth
2'10" 3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-3/4"	5-1/8" (2'10") 6-1/8" (3'0")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Smooth

CAMDEN®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6-5/8"	2-5/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-1/2"	3-1/4" (1'2") 3-3/4" (1'3") 4-1/4" (1'4")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-1/2"	4-1/4" (1'6") 5-1/4" (1'8")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
1'10" 2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15"	3-1/2" (1'0") 4-1/2" (2'0") 3-15/16" (2'2")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18"	4-15/16" (2'4")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-1/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-3/4"	4-5/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-3/4"	5-5/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	24-7/8"	5-1/2"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Oak Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


6'8" AND 7'0" DOORS

PRINCETON



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6-5/8"	2-11/16"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6-5/8"	3-5/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-1/2"	3-1/4" (1'3") 3-3/4" (1'4")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-1/2"	4-1/4" (1'6") 5-1/4" (1'8")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15"	3-1/2" (1'10") 4-1/2" (2'0")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18"	3-15/16" (2'2") 4-15/16" (2'4")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-1/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-3/4"	4-5/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-3/4"	5-5/8"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	24-7/8"	5-1/2"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Smooth

CONTINENTAL™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-7/32" (1'0") 4-7/32" (1'2")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-7/32" (1'3") 3-23/32" (1'4")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	10-9/16"	3-45/64" (1'6") 4-45/64" (1'8")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
2'2" 2'4" 2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	20"	3" (2'2") 4" (2'4") 5" (2'6")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
2'8" 2'10" 3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	24"	4" (2'8") 5" (2'10") 6" (3'0")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman


*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

SANTA FE




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	10"	4" (1'6") 5" (1'8")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18"	4" (2'2") 5" (2'4")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21"	4-1/2"	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23"	4-1/2"	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'10" 3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	24"	5" (2'10") 6" (3'0")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth

CRAFTSMAN III™



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Panel Type	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	4"	4"	N/A	4-5/8"	N/A	8-15/16"	Flat	C	Smooth
1'2" 1'3"	6'8" 6'8"	Two	1-3/8" 1-3/4"	6"	4" (1'2") 4-1/2" (1'3")	N/A	4-5/8"	N/A	8-15/16"	Flat	C	Smooth
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-1/4"	3-7/8"	N/A	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
1'6" 1'8" 1'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	10"	4" (1'6") 5" (1'8") 6" (1'10")	N/A	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	15"	4-1/2"	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'2" 2'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	17"	4-1/2" (2'2") 5-1/2" (2'4")	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'6" 2'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	21"	4-1/2" (2'6") 5-1/2" (2'8")	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'10" 3'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	25"	4-1/2" (2'10") 5-1/2" (3'0")	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth

AVALON®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	6-3/16"	2-7/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7-11/16"	3-1/8" (1'2") 3-5/8" (1'3") 4-1/8" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	8-3/4"	4-9/16" (1'6") 5-9/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
1'10" 2'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
2'2" 2'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	19-5/8"	3-3/16" (2'2") 4-3/16" (2'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
2'6"	6'8" 7'0"	Three	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
2'8" 2'10"	6'8" 7'0"	Three	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain
3'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	27-5/8"	4-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-15/16" (6'8") 9-15/16" (7'0")	MCB	Oak Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


6'8" AND 7'0" DOORS

ATHERTON®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-1/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-9/16"	3-1/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-1/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-3/16"	3-1/8"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-9/16"	3-1/8" (1'6") 4-3/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	5-9/16"	3-3/16" (1'10") 4-3/16" (2'0")	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'2" 2'4"	6'8" 7'0"	Four	1-3/8" 1-3/4"	7-9/16"	3-3/16" (2'2") 4-3/16" (2'4")	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'6"	6'8" 7'0"	Four	1-3/8" 1-3/4"	8-9/16"	4-3/16"	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'8"	6'8" 7'0"	Four	1-3/8" 1-3/4"	9-9/16"	4-3/16"	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'10" 3'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	11-9/16"	3-3/16" (2'10") 4-3/16" (3'0")	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth

PROVINCIAL®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-1/16"	N/A	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-9/16"	3-1/16"	N/A	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-1/16"	N/A	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-9/16"	3-1/16"	N/A	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-9/16"	3-1/16" (1'6") 4-3/16" (1'8")	N/A	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
1'10" 2'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	5-9/16"	3-3/16" (1'10") 4-3/16" (2'0")	4-3/8"	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
2'2" 2'4"	6'8" 7'0"	Four	1-3/8" 1-3/4"	7-9/16"	3-3/16" (2'2") 4-3/16" (2'4")	4-3/8"	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
2'6"	6'8" 7'0"	Four	1-3/8" 1-3/4"	8-9/16"	4-3/16"	4-3/8"	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
2'8"	6'8" 7'0"	Four	1-3/8" 1-3/4"	9-9/16"	4-3/16"	4-3/8"	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
2'10"	6'8" 7'0"	Four	1-3/8" 1-3/4"	10-9/16"	4-3/16"	4-3/8"	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain
3'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	11-9/16"	4-3/16"	4-3/8"	5" (6'8") 7" (7'0")	7"	9-1/4" (6'8") 11-1/4" (7'0")	O	Pine Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman


*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

STANFORD®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7"	2-7/16" (1'0") 3-7/16" (1'2") 3-15/16 (1'3") 4-7/16 (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-9/16"	3-3/16" (1'6") 4-3/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain
1'10" 2'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	5-9/16"	3-3/16" (1'10") 4-3/16" (2'0")	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain
2'2" 2'4"	6'8" 7'0"	Four	1-3/8" 1-3/4"	7-9/16"	3-3/16" (2'2") 4-3/16" (2'4")	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain
2'6"	6'8" 7'0"	Four	1-3/8" 1-3/4"	8-9/16"	4-3/16"	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain
2'8" 2'10"	6'8" 7'0"	Four	1-3/8" 1-3/4"	9-9/16"	4-3/16" (2'8") 5-3/16" (2'10")	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain
3'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	11-9/16"	4-3/16"	4-5/16"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Oak Grain

ROCKPORT




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
2'0"	6'8" 7'0"	Five	1-3/8" 1-3/4"	15-3/4"	4-1/8"	N/A	4-1/2"	N/A	8-1/2"	MCB	Smooth
2'2" 2'4"	6'8" 7'0"	Five	1-3/8" 1-3/4"	19-3/4"	3-3/8" (2'2") 4-3/8" (2'4")	N/A	4-1/2"	N/A	8-1/2"	MCB	Smooth
2'6"	6'8" 7'0"	Five	1-3/8" 1-3/4"	21-3/4"	4-1/8"	N/A	4-1/2"	N/A	8-1/2"	MCB	Smooth
2'8"	6'8" 7'0"	Five	1-3/8" 1-3/4"	23-3/4"	4-1/8"	N/A	4-1/2"	N/A	8-1/2"	MCB	Smooth
2'10" 3'0"	6'8" 7'0"	Five	1-3/8" 1-3/4"	25-3/4"	4-1/8" (2'10") 5-1/8" (3'0")	N/A	4-1/2"	N/A	8-1/2"	MCB	Smooth

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


6'8" AND 7'0" DOORS

ARLINGTON



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	5-9/16"	3-1/4"	N/A	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
1'2"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7-9/16"	3-1/4"	N/A	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	8-9/16"	3-1/2" (1'3") 4" (1'4")	N/A	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
1'6"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-9/16"	4-1/8" (1'6")	N/A	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
1'8" 1'10" 2'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	5-9/16"	5-1/8" (1'8") 3-1/2" (1'10") 4-1/2" (2'0")	4"	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
2'2" 2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	7-9/16"	3-1/2" (2'2") 4-1/2" (2'4")	4"	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-9/16"	4-1/2"	5"	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
2'8"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-9/16"	4-1/2"	5"	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth
2'10" 3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	11-9/16"	4-1/2" (2'10") 5-1/2" (3'0")	5-3/8"	4-5/8" (6'8") 6-5/8" (7'0")	6-7/8"	9-5/8" (6'8") 11-5/8" (7'0")	B	Smooth

BOSTONIAN®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7"	2-7/16" (1'0") 3-7/16" (1'2") 3-15/16" (1'3") 4-7/16" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-7/8"	3-1/16" (1'6") 4-1/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
1'10" 2'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	5-7/8"	3-1/16" (1'10") 4-1/16" (2'0")	3-7/8"	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
2'2" 2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	7-7/8"	3-3/16" (2'2") 4-3/16" (2'4")	3-7/8"	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-7/8"	4-3/16"	3-7/8"	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
2'8"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-7/8"	4-3/16"	3-7/8"	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
2'10"	6'8" 7'0"	Six	1-3/8" 1-3/4"	10-7/8"	4-3/16"	3-7/8"	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain
3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	11-7/8"	4-3/16"	3-7/8"	4-1/4" (6'8") 6-1/4" (7'0")	6-7/8"	8-1/4" (6'8") 10-1/4" (7'0")	MCB	Pine Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman


*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

BRISTOL



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-31/32"	3" (1'6") 4" (1'8")	N/A	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Six	1-3/8" 1-3/4"	5-31/32"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	3-7/8"	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth
2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	7-31/32"	4-1/8"	3-7/8"	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-31/32"	4-1/8"	3-7/8"	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth
2'8" 2'10"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-31/32"	4-1/8" (2'8") 5-1/8" (2'10")	3-7/8"	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth
3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	11-31/32"	4-1/8"	3-7/8"	4-1/8" (6'8") 6-1/8" (7'0")	6-7/8"	8-3/8" (6'8") 10-3/8" (7'0")	MCB	Smooth

COLONIAL




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7"	2-7/16" (1'0") 3-7/16" (1'2") 3-15/16" (1'3") 4-7/16" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-9/16"	3-3/16" (1'6") 4-3/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
1'10" 2'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	5-9/16"	3-3/16" (1'10") 4-3/16" (2'0")	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
2'2" 2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	7-9/16"	3-3/16" (2'2") 4-3/16" (2'4")	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-9/16"	4-3/16"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
2'8"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-9/16"	4-3/16"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
2'10"	6'8" 7'0"	Six	1-3/8" 1-3/4"	10-9/16"	4-3/16"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain
3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	11-9/16"	4-3/16"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/16" (6'8") 11-1/16" (7'0")	O	Pine Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

6'8" AND 7'0" DOORS

PREFINISHED (STAINED) SIX-PANEL



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/8"	6-1/2"	11-5/8"	O	Oak Grain
1'6" 1'8" 1'10"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-9/16"	3-1/4" (1'6") 4-1/4" (1'8") 5-1/4" (1'10")	N/A	4-1/8"	6-1/2"	11-5/8"	O	Oak Grain
2'0" 2'2"	6'8" 7'0"	Six	1-3/8" 1-3/4"	5-5/16"	4-1/2" (2'0") 5-1/2" (2'2")	4-5/16"	4-1/8"	6-1/2"	11-5/8"	O	Oak Grain
2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	7-5/16"	4-1/2"	4-5/16"	4-1/8"	6-1/2"	11-5/8"	O	Oak Grain
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-5/16"	4-1/2"	4-5/16"	4-1/8"	6-1/2"	11-5/8"	O	Oak Grain
2'8" 2'10" 3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-5/16"	4-5/8" 5-5/8" 6-5/8"	4-7/8"	4-1/8"	6-1/2"	11-5/8"	O	Oak Grain

IMPRESSION™ MIRROR DOOR



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
2'0"	6'8"	One	1-3/8"	15-5/16"	4-5/16"	N/A	4-1/2"	N/A	9-7/8"	**	Pine Grain or Smooth
2'4"	6'8"	One	1-3/8"	19-5/16"	4-5/16"	N/A	4-1/2"	N/A	9-7/8"	**	Pine Grain or Smooth
2'6"	6'8"	One	1-3/8"	21-5/16"	4-5/16"	N/A	4-1/2"	N/A	9-7/8"	**	Pine Grain or Smooth
2'8"	6'8"	One	1-3/8"	23-5/16"	4-5/16"	N/A	4-1/2"	N/A	9-7/8"	**	Pine Grain or Smooth
3'0"	6'8"	One	1-3/8"	27-5/16"	4-5/16"	N/A	4-1/2"	N/A	9-7/8"	**	Pine Grain or Smooth


Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

**Arlington Impression mirror doors have B sticking profile; Bostonian and Bristol Impression mirror doors have MCB sticking profile; Colonial Impression mirror doors have O sticking profile.


8'0" DOORS

CAMBRIDGE




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/2"	7"	9"	O	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	9-3/4"	4-1/8" (1'6") 5-1/8" (1'8")	N/A	4-1/2"	7"	9"	O	Smooth
1'10" 2'0"	8'0"	Two	1-3/8" 1-3/4"	13-3/4"	4-1/8" (1'10") 5-1/8" (2'0")	N/A	4-1/2"	7"	9"	O	Smooth
2'2" 2'4" 2'6"	8'0"	Two	1-3/8" 1-3/4"	19-3/4"	3-1/8" (2'2") 4-1/8" (2'4") 5-1/8" (2'6")	N/A	4-1/2"	7"	9"	O	Smooth
2'8" 2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	23-3/4"	4" (2'8") 5" (2'10") 6" (3'0")	N/A	4-1/2"	7"	9"	O	Smooth

PRINCETON



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	9-1/2"	4-1/4" (1'6") 5-1/4" (1'8")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth
1'10" 2'0"	8'0"	Two	1-3/8" 1-3/4"	14-15/16"	3-1/2" (1'10") 4-1/2" (2'0")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth
2'2" 2'4"	8'0"	Two	1-3/8" 1-3/4"	18-1/8"	3-15/16" (2'2") 4-15/16" (2'4")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-1/8" (2'6")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth
2'8"	8'0"	Two	1-3/8" 1-3/4"	22-13/16"	4-1/2" (2'8")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth
2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	25"	4-1/2" (2'10") 5-1/2" (3'0")	N/A	5-1/2"	3-3/4"	8-1/2"	MCB	Smooth

CONTINENTAL™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/2"	4-1/4"	11-1/4"	O	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	9-3/4"	4-1/8" (1'6") 5-1/8" (1'8")	N/A	5-1/2"	4-1/4"	11-1/4"	O	Smooth
1'10" 2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0") 6" (2'2")	N/A	5-1/2"	4-1/4"	11-1/4"	O	Smooth
2'4" 2'6"	8'0"	Two	1-3/8" 1-3/4"	20"	4" (2'4") 5" (2'6")	N/A	5-1/2"	4-1/4"	11-1/4"	O	Smooth
2'8" 2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	24"	4" (2'8") 5" (2'10") 6" (3'0")	N/A	5-1/2"	4-1/4"	11-1/4"	O	Smooth

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


8'0" DOORS

SANTA FE



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	10"	4" (1'6") 5" (1'8")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
1'10" 2'0"	8'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'2" 2'4"	8'0"	Two	1-3/8" 1-3/4"	18"	4" (2'2") 5" (2'4")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	21"	4-1/2"	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'8"	8'0"	Two	1-3/8" 1-3/4"	23"	4-1/2"	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	24"	5" (2'10") 6" (3'0")	N/A	4-3/8"	7"	9-7/8"	O	Smooth

ATHERTON®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'10" 2'0"	8'0"	Four	1-3/8" 1-3/4"	5-9/16"	3-1/4" (1'10") 4-1/4" (2'0")	4-3/8"	4-7/16"	6-31/32"	8-15/16"	O	Smooth
2'2" 2'4"	8'0"	Four	1-3/8" 1-3/4"	7-9/16"	3-1/4" (2'2") 4-1/4" (2'4")	4-3/8"	4-7/16"	6-31/32"	8-15/16"	O	Smooth
2'6"	8'0"	Four	1-3/8" 1-3/4"	8-9/16"	4-1/4"	4-3/8"	4-7/16"	6-31/32"	8-15/16"	O	Smooth
2'8"	8'0"	Four	1-3/8" 1-3/4"	9-9/16"	4-1/4"	4-3/8"	4-7/16"	6-31/32"	8-15/16"	O	Smooth
2'10" 3'0"	8'0"	Four	1-3/8" 1-3/4"	11-9/16"	3-1/4" (2'10") 4-1/4" (3'0")	4-3/8"	4-7/16"	6-31/32"	8-15/16"	O	Smooth

Rockport




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
3'0"	8'0"	6	1-3/8" 1-3/4"	25-3/4"	5-1/8"	N/A	4-1/2"	4-1/4"	10-3/8"	MCB	Smooth

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo


*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

ARLINGTON



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	8'0"	Three	1-3/8" 1-3/4"	5-1/2"	3-1/4"	N/A	4-1/4"	6-7/8"	10-1/4"	B	Smooth
1'2"	8'0"	Three	1-3/8" 1-3/4"	7-1/2"	3-1/4"	N/A	4-1/4"	6-7/8"	10-1/4"	B	Smooth
1'3" 1'4"	8'0"	Three	1-3/8" 1-3/4"	8"	3-1/2" 4"	N/A	4-1/4"	6-7/8"	10-1/4"	B	Smooth
1'6" 1'8"	8'0"	Three	1-3/8" 1-3/4"	9-13/16"	4-1/8" 5-1/8"	N/A	4-1/4"	6-7/8"	10-1/4"	B	Smooth
1'10" 2'0"	8'0"	Six	1-3/8" 1-3/4"	5-1/2"	3-1/2" 4-1/2"	4"	4-1/4"	6-7/8"	10-1/4"	B	Smooth
2'2" 2'4"	8'0"	Six	1-3/8" 1-3/4"	7-1/2"	3-1/2" 4-1/2"	4"	4-1/4"	6-7/8"	10-1/4"	B	Smooth
2'6"	8'0"	Six	1-3/8" 1-3/4"	8"	4-1/2"	5"	4-1/4"	6-7/8"	10-1/4"	B	Smooth
2'8"	8'0"	Six	1-3/8" 1-3/4"	9"	4-1/2"	5"	4-1/4"	6-7/8"	10-1/4"	B	Smooth
2'10" 3'0"	8'0"	Six	1-3/8" 1-3/4"	9-13/16"	4-1/2" 5-1/2"	5-3/8"	4-1/4"	6-7/8"	10-1/4"	B	Smooth

BOSTONIAN®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-3/8"	6-11/16"	8-1/4"	MCB	Pine Grain
1'6" 1'8"	8'0"	Three	1-3/8" 1-3/4"	9-11/16"	4-1/8" (1'6") 5-1/8" (1'8")	N/A	4-3/8"	6-11/16"	8-1/4"	MCB	Pine Grain
1'10" 2'0"	8'0"	Six	1-3/8" 1-3/4"	5-5/16"	3-1/8" (1'10") 4-1/8" (2'0")	3-9/16"	4-3/8"	6-11/16"	8-1/4"	MCB	Pine Grain
2'2" 2'4" 2'6"	8'0"	Six	1-3/8" 1-3/4"	7-11/16"	3-3/8" (2'2") 4-3/8" (2'4") 5-3/8" (2'6")	3-9/16"	4-3/8"	6-11/16"	8-1/4"	MCB	Pine Grain
2'8" 2'10" 3'0"	8'0"	Six	1-3/8" 1-3/4"	9-11/16"	4-3/8" (2'8") 5-3/8" (2'10") 6-3/8" (3'0")	3-9/16"	4-3/8"	6-11/16"	8-1/4"	MCB	Pine Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


8'0" DOORS

BRISTOL



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth
1'6" 1'8"	8'0"	Three	1-3/8" 1-3/4"	11-31/32"	3" (1'6") 4" (1'8")	N/A	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth
1'10" 2'0"	8'0"	Six	1-3/8" 1-3/4"	5-31/32"	3-5/32" (1'10") 4-5/32" (2'0")	3-3/4"	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth
2'2" 2'4"	8'0"	Six	1-3/8" 1-3/4"	7-31/32"	3-5/32" (2'2") 4-5/32" (2'4")	3-3/4"	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth
2'6"	8'0"	Six	1-3/8" 1-3/4"	8-31/32"	4-5/32"	3-3/4"	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth
2'8"	8'0"	Six	1-3/8" 1-3/4"	9-31/32"	4-5/32"	3-3/4"	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth
2'10" 3'0"	8'0"	Six	1-3/8" 1-3/4"	10-31/32"	4-5/32" (2'10") 5-5/32" (3'0")	3-3/4"	5-1/16"	6-7/8"	8-7/16"	MCB	Smooth

COLONIAL



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	8'0"	Three	1-3/8" 1-3/4"	9-9/16"	4-3/16"	N/A	4-1/4"	7"	9"	O	Pine Grain
1'10" 2'0"	8'0"	Six	1-3/8" 1-3/4"	5-9/16"	2-3/16" (1'8") 3-3/16" (1'10") 4-3/16" (2'0")	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
2'2" 2'4"	8'0"	Six	1-3/8" 1-3/4"	7-9/16"	3-3/16" (2'2") 4-3/16" (2'4")	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
2'6"	8'0"	Six	1-3/8" 1-3/4"	8-9/16"	4-3/16"	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
2'8"	8'0"	Six	1-3/8" 1-3/4"	9-9/16"	4-3/16"	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
3'0"	8'0"	Six	1-3/8" 1-3/4"	11-9/16"	4-3/16"	4-3/8"	4-1/4"	7"	9"	O	Pine Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

BIFOLD DOORS

BIFOLDS




Door Design	Heights*	# of Panels	Thickness	Widths* 2 doors or 1 unit	Widths* 4 doors or 2 units
Atherton®	6'7"; 6'11"; 7'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Arlington	6'7"; 6'11"; 7'11"	Three	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Avalon®	6'7"; 6'11"	Three	1-3/8"	2'0"; 2'6"; 3'0"	4'0"; 5'0"; 6'0"
Bostonian®	6'7"; 6'11"; 7'11"	Three	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Bristol	6'7"; 6'11"; 7'11"	Three	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Cambridge	6'7"; 6'11"; 7'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Camden®	6'7"; 6'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Colonial	6'7"; 6'11"; 7'11"	Three	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Continental™	6'7"; 6'11"; 7'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Craftsman III™	6'7"	Two	1-3/8"	1'8", 1'10", 2'0"; 2'2", 2'4"; 2'6"; 2'8", 2'10", 3'0"	4'0"; 5'0"; 6'0"
Princeton	6'7"; 6'11"; 7'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Provincial®	6'7"; 6'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Rockport	6'7"; 6'11"	Five	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"
Santa Fe	6'7"; 6'11"; 7'11"	Two	1-3/8"	2'0"; 2'4"; 2'6"; 2'8"; 3'0"	4'0"; 4'8"; 5'0"; 5'2"; 5'6"; 6'0"

* All panel, inner stile, top rail and lock rail measurements will match those listed above. Outer stile measurements may vary 1/4" (depending on pre-fit). All bottom rail measurements will be 1" shorter than the measurements listed above in order to accommodate track and hardware.

Bifolds are available in alternate heights and widths. Please contact your local JELD-WEN facility for specifications and availability of alternate sizes. All bifolds are boxed (or end-capped) with track and hardware included.

COMMERCIAL WIDE STILE



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Stile	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
3'0" Continental	6'8" 7'0"	Two	1-3/8" 1-3/4"	24"	6"	N/A	5-1/2" (6'8") 7-1/2" (7'0")	4-3/16"	11-1/4"	O	Smooth
3'0" Arlington	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-5/16"	6-3/4"	5"	5-9/16" (6'8") 7-9/16" (7'0")	6-7/16"	11-1/4"	B	Smooth
3'0" Colonial	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-1/8"	6-7/16"	4-7/8"	4-1/2" (6'8") 6-1/2" (7'0")	6-7/16"	11-1/4"	O	Oak Grain

Sticking Profile: B=Beaded, MCB=Modified Cove and Bead, O=Ovolo, C=Craftsman

*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-3/4" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.