

Client: Dauntless Molds, Covina, California

“A One Stop company that will take your product from prototype to final production mold.”

Equipment running with MATTEI EMS 200 since 1989 with 64,737 hours!

- Sandblaster
- CNC Machines-Mill
- Lathe
- Surface Grinder
- Wire EDM
- Drilling



Electric motor replaced after 17 years per LANS Company. “We call LANS Company when we have any issues and they arrive within hours and set-up a portable unit as the issue is resolved. They conduct regular service during our lunch hour to avoid production disruption.” Said John

Standard Equipment and Features	Manual motor starter with thermal overload
	3 phase voltages are 230 and 460vAC
	1 phase voltage (S models) is 230vAC
	TEFC motor
	Integrated oil cooler
	Frame mounted for easy installation
	Hydraulically actuated intake valve for precise control of intake air.
	Air-cooled - air after cooler with 10° F approach temperature of discharge air.
	Integrated high efficiency coalescing oil separator filter. Maximum oil carryover is 2-5 PPM.
	Pressure gauge
	Oil level sight glass.
	Intake air filter
	Condensate separator with auto-drain
	Built in thermostatic bypass valve
Minimum pressure non-return valve	
Standard Safety Features	Motor over-current protection
	High temperature shutdown switch
	Safety relief valve
Electrical Controls	Manual motor starter
	Adjustable thermal overload
	Control voltage transformer with fuses
	Start and stop buttons
	High temperature shutdown