



## ***HSM SECURIO P36***



From [ShreddingMachines.co.uk](http://ShreddingMachines.co.uk) - The largest independent supplier of shredders in the UK

## HSM SECURIO P36

Mobile, high performance model for open-plan offices. Multi-function operating button, reversing button and integrated button lock. Auto-reverse in the event of a paper jam. Folding safety element with contact protection and integrated service flap. Automatic oiler for cutting unit (particle cut version only). Separate CD cutting unit (security level 3) and metal detection, depending on security level. Economic energy management (EMCS). Filling level display through inspection window. Large collection volume. With removable, reusable waste bag. Special CD waste container for correctly sorted separation of the shredded material (optional). Made in Germany.

Product type description	SECURIO P36 3,9mm	SECURIO P36 5,8mm
Order number	1850111	1851111
EAN Code	4026631032254	4026631032285
Shredder material		
Cutting type	strip cut	strip cut
Security level	2	2
Cutting width	3.9 mm	5.8 mm
Particle length		
Cutting capacity (70g/m <sup>2</sup> )	37 - 39 sheet	47 - 49 sheet
Cutting capacity (80g/m <sup>2</sup> )	31 - 33 sheet	39 - 41 sheet
Intake width	330 mm	330 mm
Container volume	145 l	145 l
Cutting speed	90 mm/s	90 mm/s
Noise level (idle operation)		60 dB
eclass 5.1	24320704	24320704
Power consumption of the motor	1600 W	1600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Depth	550 mm	550 mm
Width	580 mm	580 mm
Height	936 mm	936 mm
Weight	64 kg	64 kg

**HSM SECURIO P36**

Product type description	SECURIO P36 4,5x30mm	SECURIO P36 1,9x15mm
Order number	1853111	1852111
EAN Code	4026631032360	4026631032292
Shredder material		
Cutting type	particle cut	particle cut
Security level	3	4
Cutting width	4.5 mm	1.9 mm
Particle length	30,00 mm	15 mm
Cutting capacity (70g/m <sup>2</sup> )	29 - 31 sheet	18 - 20 sheet
Cutting capacity (80g/m <sup>2</sup> )	25 - 27 sheet	15 - 17 sheet
Intake width	330 mm	330 mm
Container volume	145 l	145 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)		
eclass 5.1	24320704	24320704
Power consumption of the motor	1600 W	1600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Depth	550 mm	550 mm
Width	580 mm	580 mm
Height	936 mm	936 mm
Weight	68 kg	68 kg