



	<i>B18</i>	<i>B19</i>	<i>B23i</i>	<i>H25</i>	<i>H27i</i>	<i>H24d</i>	<i>S14</i>	<i>C19</i>	<i>T23</i>	<i>T25i</i>	<i>T30i</i>	<i>D21d</i>
DESCRIPTION	Originally designed as a basic machine to run Walker discharge and mulching decks, the B18 has evolved into one of the most agile and versatile tractors in power equipment. Its hillside performance is unmatched by competitive machines in the industry.	The B19 is a simple, clean design using many of the same principles as the Walker original. Includes a powerful Kohler Command engine and simplified drive train. Side discharge or mulch decks can easily be installed using a quick connect PTO drive shaft.	The B23i adds a 23-hp Kohler EFI to the agile MB lineup to increase available power and efficiency for using Walker discharge and mulching decks up to 56" and a variety of seasonal attachments. The B23i stands alone in its class as a compact mower design with EFI technology and a powerful engine.	Built with the speed and price tag of a mid-mount but the superior design of a front cut, the H25 features Walker's proven, comfortable steering configuration, and high quality grass-cutting. It also has a tilt-up deck and body, making the H25 a must-have for landscape professionals, municipalities, and acreage owners.	Two strong design advantages—front-cut mowing and Kohler's Delphi electronic fuel injection system—have been brought together in the H27i. It is the ideal combination of horsepower, productivity and fuel efficiency.	With superior fuel efficiency and the maximum torque of the state-of-the-art Yanmar® Minimax Engine, the H24d is an aggressive competitor in overall job-time and cost savings.	The S-Series is the original design of the Walker; built to be compact and maneuverable. It uses a smaller engine and simplified drive train and shares most of the features of the high-performance models. The S14 is a great machine for homeowners and large property owners.	A durable design combined with the powerful engine of the C19 provides agility, maneuverability, and high-capacity mowing. This model is a popular machine for entry into commercial mowing.	Popular with lawn maintenance professionals, the T23 offers a perfect balance of power, agility, durability, and versatility for a wide range of mowing applications, making it a popular choice for over twenty years.	A powerful air-cooled engine with EFI technology delivers a responsive, fuel efficient performance. This mower provides powerful acceleration and throttle response. Built-in diagnostics and service light on the instrument panel simplify troubleshooting.	Operators can expect easy starting, consistent running temperatures, and user-friendly maintenance from this top-of-the-line mower. A combination of liquid cooling and EFI from Kohler's 30-HP Aegis engine provides increased engine life, power, and better fuel economy compared to air-cooled engines.	A top-of-the-line Kubota diesel engine at the core of the D21d provides long life and fuel economy. It is a hard working, proven performer for commercial and municipal operators.
ENGINE/MODEL	Briggs & Stratton Vanguard V-Twin, 2 cyl.	Kohler Command Pro CH621, 2 cyl.	Kohler Command Pro EFI ECH730, 2 cyl.	Kohler Command Pro CH740, 2 cyl.	Kohler Command Pro EFI ECH749, 2 cyl.	Yanmar 3TNM72, 3 cyl.	Subaru Robin EX40, 1 cyl.	Kohler Command Pro CH621, 2 cyl.	Kohler Command Pro CH680, 2 cyl.	Kohler Command Pro EFI ECH740, 2 cyl.	Kohler Aegis EFI LH775 Liquid Cooled, 2 cyl.	Kubota D722, 3 cyl.
MAX POWER	18 hp @ 3600 rpm	19 hp @ 3600 rpm	23 hp @ 3600 rpm	25 hp @ 3600 rpm	26.5 hp @ 3600 rpm	23.6 hp @ 3600 rpm	14 hp @ 3600 rpm	19 hp @ 3600 rpm	22.5 hp @ 3600 rpm	25 hp @ 3600 rpm	30 hp @ 3600 rpm	20.9 hp @ 3600 rpm
DISPLACEMENT	570cc (34.8 cu. in.)	624cc (39.1 cu. in.)	747cc (45 cu. in.)	725cc (44 cu. in.)	747cc (45 cu. in.)	904cc (55.2 cu. in.)	404cc (24.65 cu. in.)	624cc (39.1 cu. in.)	674cc (41.1 cu. in.)	747cc (45 cu. in.)	747cc (45.6 cu. in.)	719cc (43.9 cu. in.)
MAX TORQUE	29.5 ft lbs	32.2 ft lbs	38.1 ft lbs	39.2 ft lbs	40 ft lbs	40.9 ft lbs	19.9 ft lbs	32.2 ft lbs	36.8 ft lbs	38.8 ft lbs	44.6 ft lbs	34 ft lbs
FUEL	Gas (E10 max)	Gas (E10 max)	Gas (E10 max)	Gas (E10 max)	Gas (E10 max)	Diesel (2-D)	Gas (E10 max)	Gas (E10 max)	Gas (E10 max)	Gas (E10 max)	Gas (E10 max)	Diesel (2-D)
FUEL CAPACITY (US GAL)	2.8 (10.6 liter)	2.8 (10.6 liter)	4.7 (17.8 liter)	9.4 (35.6 liter)	9.4 (35.6 liter)	9.4 (35.6 liter)	1.9 (7.2 liter)	2.8 (10.6 liter)	4.7 (17.8 liter)	4.7 (17.8 liter)	4.7 (17.8 liter)	4.7 (17.8 liter)
COOLING SYSTEM	Air	Air	Air	Air	Air	Liquid, Radiator	Air	Air	Air	Air	Liquid, Radiator	Liquid, Radiator
LUBRICATION SYSTEM	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Mechanical Splash Lube	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter	Full-Pressure w/ Filter
GROUND SPEED (MPH)	8	8	8	10	10	10	6.5	7	7	7	7	7
BLADE CLUTCH/BRAKE	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake	Manual Belt Tightener/ Band Brake
CUTTING WIDTH (INCHES)	36" to 56" Side Discharge, 36" to 48" Mulching (9 Decks)	36" to 56" Side Discharge, 36" to 48" Mulching (9 Decks)	36" to 74" Side Discharge, 36" to 52" Mulching (13 Decks)	Dedicated 60" Side Discharge or 52" Rear Discharge/Mulching Deck (Deck Arm Adapter Kit available for using other decks)	Dedicated 60" Side Discharge or 52" Rear Discharge/Mulching Deck (Deck Arm Adapter Kit available for using other decks)	Dedicated 60" Side Discharge or 52" Rear Discharge/Mulching Deck (Deck Arm Adapter Kit available for using other decks)	36" or 42" GHS, Side Discharge, or Mulching (7 Decks)	36" to 48" GHS, 36" to 62" Side Discharge, 36" to 52" Mulching (13 Decks)	36" to 52" GHS, 36" to 74" Side Discharge, 36" to 52" Mulching (18 Decks)	36" to 52" GHS, 36" to 74" Side Discharge, 36" to 52" Mulching (18 Decks)	36" to 52" GHS, 36" to 74" Side Discharge, 36" to 52" Mulching (18 Decks)	36" to 52" GHS, 36" to 74" Side Discharge, 36" to 52" Mulching (18 Decks)
GHS BLOWER/CATCHER SIZE	No GHS Option	No GHS Option	No GHS Option	No GHS Option	No GHS Option	No GHS Option	12.75"/7.0 Bu.	10.5"/7.0 Bu.	10.5"/10.0 Bu.	10.5"/10.0 Bu.	10.5"/10.0 Bu.	10.5"/10.0 Bu.
DRIVE TIRES	18 x 8.50-10	18 x 8.50-10	18 x 8.50-10	22 x 10.50-12	22 x 10.50-12	22 x 10.50-12	18 x 7.00-8	18 x 8.50-10	18 x 9.50-8	18 x 9.50-8	18 x 9.50-8	18 x 9.50-8
OUTSIDE DIMENSIONS	40.5 H x 44 W x 82 L ^[1]	40.5 H x 44 W x 82 L ^[1]	40.5 H x 44 W x 82 L ^[1]	46.5 H x 62 W x 107 L ^[2]	46.25 H x 62 W x 107 L ^[2]	46.25 H x 62 W x 107 L ^[2]	44.5 H x 43 W x 89 L ^[1]	47.25 H x 43 W x 89 L ^[1]	49 H x 49 W x 91 L ^[3]	49 H x 49 W x 91 L ^[3]	49 H x 49 W x 91 L ^[3]	49 H x 49 W x 91 L ^[3]
WHEEL BASE (TRACTOR)	39.5 in.	39.5 in.	39.5 in.	45 in.	45 in.	45 in.	42.25 in.	42.25 in.	42.25 in.	42.25 in.	42.25 in.	42.25 in.
TRACTOR WIDTH	38.5 in.	38.5 in.	38.5 in.	46.5 in.	46.5 in.	46.5 in.	36 in.	37.75 in.	39.25 in.	39.25 in.	39.25 in.	39.25 in.
SD TRACTOR WEIGHT	572 lbs.	586 lbs.	594 lbs.	752 lbs.	753 lbs.	985 lbs.	N/A	N/A	664 lbs.	672 lbs.	N/A	787 lbs.
GHS TRACTOR WEIGHT	N/A	N/A	N/A	N/A	N/A	N/A	595 lbs.	734 lbs.	795 lbs.	799 lbs.	898 lbs.	959 lbs.
TRACTOR-DECK WEIGHT	768 lbs. ^[1]	782 lbs. ^[1]	790 lbs. ^[1]	1,197 lbs. ^[2]	1,198 lbs. ^[2]	1,430 lbs. ^[2]	788 lbs. ^[1]	925 lbs. ^[1]	1,014 lbs. ^[3]	1,018 lbs. ^[3]	1,117 lbs. ^[3]	1,178 lbs. ^[3]

^[1]Dimensions and weight shown with 42" deck with discharge shield folded or collection deck ^[2]Dimensions and weight shown with 60" deck with discharge shield folded ^[3]Dimensions and weight shown with 48" collection deck

Notes



STANDARD FEATURES

- Industrial grade engines, all of which are OHV, exhaust emission certified and pressure lubricated (MS engine uses splash lubrication)
- Hydrostatic transmissions and gear drive axle proven in years of service (3-year warranty). Hydro-Gear® transaxles feature a 3-year warranty for H-Series tractors and 2-year warranty on B-Series tractors
- All gearboxes use ball or roller bearings and are permanently lubricated
- Durable all-welded steel frame [3/8" x 2" main frame (2-1/2" MD/MT)] or 3/16 plate steel uni-body frame (MB/MH)
- Body (14GA) and deck (11GA) are welded steel construction
- Industrial grade drive belts can easily be removed and replaced in field
- Belts tensioned by self-adjusting, spring-loaded idlers
- Simple mechanical belt tightener PTO clutch and brake
- Quick disconnect, splined PTO drive shaft connection speeds deck installation (bolt-on PTO tube used on B18 and S14)
- Shear pin in shock protection for blade drive
- Parking brake uses mechanical lock in axle
- GHS air exhaust screen is removable for easy cleaning
- Gas springs with dampening action are used on grass catcher door and tilt (GHS model), and body tilt-up
- Tapered roller bearings are used on deck caster wheel pivots
- Suspension seat is standard on Models H24d, H25, H27i, D21d, and T30i

ACCESSIBLE

Standard on all Walker decks is the tilt-up function. This feature makes blade and deck housing maintenance easy and safe. This is a considerable advancement in mower design when compared to jacking up the mower and laying on the ground to access the deck.



Tilt-Open and Tilt-Up bodies quickly expose engine and drive train for service and easy maintenance.

COLLECTION VS. NON-COLLECTION

Two types of riding tractors are offered – Collection utilizing the Walker Grass Handling System (GHS) and Non-collection exclusively using Discharge and Mulching decks.

COLLECTION (GHS)

Grass handling decks efficiently deliver cut material to the internal blower which then propels and compacts the debris into the catcher box. Discharge and Mulching decks can be installed on GHS tractors when catching is not required.



NON-COLLECTION

When grass collection is not needed, configurations without the GHS system utilize Discharge and Mulching decks.



ADD-ONS COMPATIBILITY LIST

ATTACHMENTS

	S	C	T	D	B	H
48" Dozer Blade Attachment	•	•	•	•	•	
Operator Soft Cab		•	•	•		
ROPS Kit						•
36" Single-Stage Snow Blower	•	•	•	•	•	

DECK ATTACHMENTS

Dethatcher
Boom Sprayer

Compatible with gear drive decks up to 52"
Compatible with decks between 42" and 62"

IMPLEMENTS

Implement Hitch Mount		•	•	•		
Debris Blower		•	•	•		
46" Dozer Blade		•	•	•		
Loader Bucket		•	•	•		
47" Rotary Broom		•	•	•		•
42" Two-Stage Snow Blower		•	•	•		
60" Dozer Blade		•	•	•		•
H-Series Implement Hitch Mount						•
H-Series 50" Two-Stage Snowblower						•
H-Series 60" Rotary Broom						•

OPTIONS

Comfort Seat		•	•	•	•	
Suspension Seat		•	•	•		
Arm Rests	•	•	•	•	•	
Headlights	•	•	•	•	•	•
Instrument Panel Cover			•	•		
Hi-Dump® Kit			•	•		
Power Dump Kit			•	•		
No-Catch Deflector	•		•	•		
GHS Blower Lockout		•	•	•		
GHS Large Hole Screen	•	•	•	•		
Catcher Bins			•	•		
Mechanical Deck Lift		•	•	•		
Power Deck Lift			•	•		
Narrow Drive Tires		•	•	•	•	
Wide Drive Tires	•		•	•		
Low Profile Tires	•	•	•	•	•	
All Terrain Tires	•	•	•	•	•	
All Trail Tires						•
Tire Chains	•	•	•	•	•	•
Single Wide Tail Wheel			•	•		
Spread Axle Tail Wheels		•	•	•		
Tail Weight		•	•	•	•	•
Tail Wheel Lock			•	•		

DECK OPTIONS

Manual Deck Height Adjuster
Curb Jumper
Adjustable Footrests
Deck Cuff Kit
Break Away Blades
Foamed Deck Tires

Compatible with decks up to 62"
Compatible with gear drive decks between 42" and 48"
Compatible with gear drive decks up to 52"
Compatible with collection decks C36R, C48, C52R
Compatible with 42", 46", 54", 56" side discharge decks
Compatible with decks up to 56"

PN: 6895-61 — © Walker Manufacturing Co. — www.walkermowers.com



Quick Reference Guide

