

Product Name: ASACLEAN™ SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016

Form # 056E

1/7

1. IDENTIFICATION

Product Name: ASACLEAN™ U, newE, newEX, SA, C, SL

SDS Number: ASA-Gr1-US-002

RESPONSIBLE PARTY IN THE USA:

Company Name: Sun Plastech Inc.

Address: 1055 Parsippany Blvd.
Parsippany, NJ 07054

Telephone number: 1-973-257-1999 Facsimile number: 1-973-257-1011 **EMERGENCY TELEPHONE NUMBER:**

CHEMTREC

Telephone number: 1-800-424-9300 (US/Canada) or 1-703-527-3887 (International)

RECOMMENDED APPLICATION:

Purging compound for thermoplastic injection molding machines and extruders

RESTRICTION ON USAGE:

Usage for the following applications is strictly prohibited:

-Being implanted into human body.

-Invasive or non-invasive contact with human body (including blood, body fluids, etc.) continuously for 30 days or more

2. HAZARD(S) IDENTIFICATIONS

GHS CLASSIFICATION:

PHYSICAL AND CHEMICAL HAZARDS:

Combustible solid: Classification not possible Metal-corrosive material: Classification not possible

Those items except the above are out of scope for classification.

HEALTH TOXICITY:

Acute toxicity (oral): Classification not possible Acute toxicity (dermal): Classification not possible Acute toxicity (Inhalation: gases): Classification not possible Acute toxicity (Inhalation: vapors): Classification not possible Acute toxicity (Inhalation: dusts / mists): Classification not possible Skin corrosion / irritation: Classification not possible Serious eve damage / eve irritation: Classification not possible Respiratory sensitization: Classification not possible Skin sensitization: Classification not possible Germ cell mutagenicity: Classification not possible Carcinogenicity: Classification not possible Reproductive toxicity: Classification not possible

Specific target organ / systemic toxicity (single exposure): Classification not possible Specific target organ / systemic toxicity (repeated exposure): Classification not possible

Aspiration Hazard: Classification not possible

HAZARDOUS TO THE AQUATIC ENVIRONMENT:

Toxicity to the aquatic environment (acute): Classification not possible Toxicity to the aquatic environment (chronic): Classification not possible

GHS LABEL ELEMENTS:

Pictograms: None Signal word: None

Hazard statements: None



Product Name: ASACLEAN™ SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016

Form # 056E

2/7

Precautionary statements: None

[First-aid]: Refer to "4. FIRST-AID MEASURES"[Storage]: Refer to "7. HANDLING AND STORAGE"[Disposal]: Refer to "13. DISPOSAL CONSIDERATIONS"

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classification of the substance or mixture: Mixture

Grade	Composition	Content	CAS No.
Type		%	
U	Styrenic resin	More than 50	Rgstd/Non-disclosed
	Resin additives	Less than 20	Rgstd/Non-disclosed
	Inorganic additives	Less than 30	Rgstd/Non-disclosed
newE	Styrenic resin	More than 80	Rgstd/Non-disclosed
	Resin additives	Less than 10	Rgstd/Non-disclosed
	Other additives	Less than 10	Rgstd/Non-disclosed
newEX	Styrenic resin	Less than 50	Rgstd/Non-disclosed
	Resin additives	Less than 10	Rgstd/Non-disclosed
	Inorganic additives(Include GF)	Less than 50	Rgstd/Non-disclosed
	Other additives	Less than 10	Rgstd/Non-disclosed
SA	Styrenic resin	More than 80	Rgstd/Non-disclosed
	Resin additives	Less than 20	Rgstd/Non-disclosed
С	Styrenic resin	Less than 50	Rgstd/Non-disclosed
	Resin additives	Less than 10	Rgstd/Non-disclosed
	Inorganic additives	More than 50	Rgstd/Non-disclosed
	Other additives	Less than 10	Rgstd/Non-disclosed
SL	Styrenic resin	More than 80	Rgstd/Non-disclosed
	Resin additives	Less than 10	Rgstd/Non-disclosed
	Inorganic additives	Less than 10	Rgstd/Non-disclosed
	Other additives	Less than 10	Rgstd/Non-disclosed

The specific chemical identities and percentages of composition have been withheld as trade secrets.

4. FIRST-AID MEASURES

INHALATION: When feeling sick by inhaling gas and / or fumes generated from molten

plastics, move the victim from the area to fresh air and wait for recovery. Seek

medical attention.

SKIN CONTACT: For skin contact with powder or pellets, wash thoroughly with soap and water.

For skin contact with molten plastic, immediately wash thoroughly and cool down with soap and water. Hardened resin on the skin should not

be forcibly peeled off. Seek medical attention if there is a burn.

EYE: Because there is a possibility of damaging the eyeball, immediately flush the

affected eye(s) with copious quantity of clean water for at least 15 minutes. Remove contact lens(es) at once unless the lens(es) is/are stuck to eye (s).

INGESTION: If swallowed, induce vomiting. Seek immediate medical attention if

abnormality is felt.

PROTECTION TO FIRST-AIDERS: Ventilate gas generated from the molten plastics. Wear

protective gear.



Product Name: ASACLEAN™ SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016

Form # 056E

3/7

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, water-jet and other various fire extinguishers. **SPECIFIC HAZARDS / TOXICITY AT FIRE:** May emit gases including carbon monoxide, carbon

dioxide, nitrogen oxide, etc.

FIRE-FIGHTING INSTRUCTIONS: Extinguish fire from a windward direction

PROTECTION TO FIRE-FIGHTERS: Wear protective clothing. In case of large amount of gases,

emitted, breathing apparatus should be used.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION: When both pellets and powders are spilled on the floor, promptly

clean to prevent slipping.

ENVIRONMENTAL NOTES: Due to possible adverse affects to fish, birds, etc., immediately

clean up any material that may have spilled into bodies of water.

REMOVAL METHOD: Sweep with vacuum cleaner, broom, etc., and dispose of properly.

PREVENTIVE MEASURE OF SECONDARY DISASTER: None

7. HANDLING AND STORAGE

HANDLING: Application temperature: Refer to Table 1 on page 7 of 7.

- 1) Though there is less likelihood of pellets igniting under normal temperatures, avoid any fire/ignition sources in the vicinity of the product and perform adequate housekeeping to keep the surrounding clean.
- 2) Cool down purge pile with water.
- 3) Ensure proper ventilation since resins processed at high temperatures will emit gases. Local ventilation preferably should be provided.

STORAGE:

SUITABLE STORAGE CONDITION:

- 1) Store material in away from heat and ignition sources.
- 2) Avoid direct sunlight.
- 3) Store material away from high temperatures and high humidity.

SAFE CONTAINER MATERIAL FOR PACKING: Use appropriate storage containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide local exhaust ventilation for comfortable working

environments.

CONTROL OF CONCENTRATION: Not established

EXPOSURE LIMITS: Although ACGIH has not established the allowable

concentration for dust, the following values are considered

to be appropriate for operation.

ACGIH (2014 version):

Allowable concentration as general dust (TWA) INHALABLE PARTICULATE: 10mg / m³ RESPIRABLE PARTICULATE: 3 mg / m³

INDIVIDUAL PROTECTION MEASURES:

Respiratory organ: Box respirator for organic gas should be worn when working in areas

where inhalation of high temperature gases is possible.

For hand: Wear heat-proof gloves when molten resin is handled.

For eye: During purging operation, resin-made glasses and resin-made goggles

with side-shields should be worn.

For skin & body: Work wear with long sleeves is recommended when molten resin is

handled.



Product Name: ASACLEAN™ SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016 Form # 056E

4/7

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

Physical form: Solid Shape: Pellet

Color: Milky white ~ light yellow, (SL: Transparency and the white are mixed.)

Odor: Specific slight odor

Odor threshold: Not available pH: Not applicable

Melting Point: Does not exhibit sharp melting point, but softens at about 80°C

for SL and about 130°C for other types.

Decomposition Temperature: No data Flash Point: 380°C Auto-ignition Temperature: 490°C

Explosive Limits

Lower Limit: Not applicable (Lower limit for dust explosion: 35g/m³)

Upper Limit: Not applicable

Specific Gravity: Refer to Table 1 on page 7 of 7.

Solubility:

Water: Insoluble

Other solvent: Soluble in methyl ethyl ketone, cyclohexanone, etc. (except for inorganic

content).

Vapor pressure: Not available Vapor density: Not available Relative density: Not available Partition coefficient: Not available Viscosity: Not available

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal temperature.

REACTIVITY: None CONDITIONS TO AVOID:

- -Avoid using outside the specified range for the use temperature.
- -Do not let sit in barrel for more than 30 minutes at temperatures above 300°C for U, newE, SA, C, SL
- Do not let sit in barrel for ANY amount of time at ANY temperature for newEX.

MATERIALS TO AVOID: None

HAZARDOUS / TOXIC DECOMPOSITION PRODUCTS:

-May produce carbon monoxide, carbon dioxide, nitrogen oxide, etc. during incineration. May produce methyl methacrylate during pyrolysis.



Product Name: ASACLEAN™ SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016 Form # 056E

5/7

11. TOXICOLOGICAL INFORMATION

			Inorganic	.	Composition
	Base Resin	Resin Additives	Additives (Including GF)	Other Additives	(Product)
Acute Toxicity	Classification	Classification	Classification	Classification	Classification
(oral)	not possible	not possible	not possible	not possible	not possible
(Oral)	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Acute Toxicity (Dermal)	Classification	Classification	Classification	Classification	Classification
	not possible	not possible	not possible	not possible	not possible
(Definal)	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Acute Toxicity	Classification	Classification	Classification	Classification	Classification
(Inhalation: gases)	not possible	not possible	not possible	not possible	not possible
(IIIIIaiaiioII. gases)	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Acute Toxicity	Classification	Classification	Classification	Classification	Classification
Acute Toxicity (Inhalation: vapor)	not possible	not possible	not possible	not possible	not possible
(IIIIIaiaiioii. vapoi)	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Acute Toxicity	Classification	Classification	Classification	Classification	Classification
(Inhalation:	not possible	not possible	not possible	not possible	not possible
dust / mist)	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Skin Corrosion /	Classification	Classification	Cotogory 2	Classification	Classification
Irritation	not possible	not possible	Category 2	not possible	not possible
IIIIalion	(No data available)	(No data available)	(newEX)	(No data available)	Remarks*
Ossiswa Eva Damana	Classification	Classification	Category 2B	Classification	Classification
Serious Eye Damage/	not possible	not possible		not possible	not possible
Eye Irritation	(No data available)	(No data available)	(newEX)	(No data available)	Remarks*
Doonirotory or Ckin	Classification	Classification	Classification	Classification	Classification
Respiratory or Skin	not possible	not possible	not possible	not possible	not possible
Sensitization	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Corm Coll	Classification	Classification	Classification	Classification	Classification
Germ Cell	not possible	not possible	not possible	not possible	not possible
Mutagenicity	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
	Classification	Classification	Classification	Classification	Classification
Carcinogenicity	not possible	not possible	not possible	not possible	not possible
	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Damma di catico	Classification	Classification	Classification	Classification	Classification
Reproductive	not possible	not possible	not possible	not possible	not possible
Toxicity	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Specific Target Organ /	Classification	Classification	Category 3	Classification	Classification
Systemic Toxicity	not possible	not possible	Respiratory	not possible	not possible
(single exposure)	(No data available)	(No data available)	tract irritation	(No data available)	Remarks*
	,	,	(newEX)	· ·	
Specific Target Organ /	Classification	Classification	Classification	Classification	Classification
Systemic Toxicity (repeated exposure)	not possible	not possible	not possible	not possible	not possible
	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)
Respiratory	Classification	Classification	Classification	Classification	Classification
Toxicity	not possible	not possible	not possible	not possible	not possible
by Inhalation	(No data available)	(No data available)	(No data available)	(No data available)	(No data available)

(Remarks):

^{*:} Even though the product is classifiable for some items if looked solely as a GF (glass fiber) unit, it's labeled as "Classification not possible" as a form of kneaded-pellet product since it (GF content) is judged as having little effect.



Product Name: ASACLEAN™ SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016

Form # 056E

6/7

12. ECOLOGICAL INFORMATION

	Dogo Dogin	Resin	Inorganic	Other Additives	Composition
	Base Resin	Additives	Additives		(Product)
Hazardous to The	Classification	Classification	Classification	Classification	Classification
Aquatic Environment	not possible				
(Acute)	(No data available)				
Hazardous to The	Classification	Classification	Classification	Classification	Classification
Aquatic Environment	not possible				
(Chronic)	(No data available)				

13. DISPOSAL CONSIDERATIONS

Refer to all federal, state and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

14. TRANSPORT INFORMATION

LAND TRANSPORT

ADR, RID, DOT

Class: Not applicable Packing Group (PG): Not applicable UN Number: Not applicable

Proper Shipping Name: ASACLEAN (Purging Compound)

SEA TRANSPORT

IMDG

Class: Not applicable Packing Group(PG): Not applicable UN Number: Not applicable

Proper Shipping Name: ASACLEAN (Purging Compound)

AIR TRANSPORT

ICAO/IATA

Class: Not applicable Packing Group (PG): Not applicable UN Number: Not applicable

Proper Shipping Name: ASACLEAN (Purging Compound)

15. REGULATORY INFORMATION

USA

OSHA: Hazard Communication Rule, 29 CFR, 1910.1200.

TSCA Inventory: All ingredients are listed or exempt.

EPCRA Section 312/313: No ingredients are listed above reportable quantities. CERCLA Hazardous Substances: No ingredients are listed above reportable quantities.

Canadian Environmental Protection Act, 1999

HMIS

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.



SDS No.: ASA-Gr1-US-002 First issue: August 28, 2014 Revised: April 1, 2016 **SAFETY DATA SHEET** Form # 056E

7/7

Product Name: ASACLEAN™

16. OTHER INFORMATION

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Asahi Kasei Corporation. It relates only to the specific product designated herein, and does not relate to use in combination with any other material or in any process. Asahi Kasei Corporation assumes no legal responsibility for use of or reliance upon this information. According to our company policy, both usages of this product to purge when producing the following medical equipment written below and to produce general medical equipment itself are strictly prohibited.

- Being implanted into human body.
- Invasive (human body) applications
- Contact with human body (including blood, body fluid, etc.) continuously for 30 days or more. For any other medical-related applications, please contact the Asaclean Business Department. (Phone +81-3-3296-3274).

For any query with respect to what is contained herein, please refer to:

Asaclean Technical Group

Asahi Kasei Corporation

1-3-1 Yakoh, Kawasaki-ku, Kawasaki City, Kanagawa, 210-0863, Japan;

Tel: +81-44-271-2503, Fax: +81-44-271-2333

(Table1)

Grade Type	Temperature Range for Use (Unit: °C)	Specific Gravity (23°C)	
U	180~360	1.25	
newE	160~300	1.06	
newEX	200~360	1.48	
SA	180~360	1.04	
С	180~360	1.63	
SL	150~300	1.05	

Records of revision

April 1, 2016 : Changed company name (Asahi Kasei Corporation)