## 1436/1446/2456/2466

## FIXED/ARCHITECTURAL VINYL WINDOW

## MAKE YOUR VISION A REALITY



## **FEATURES & BENEFITS:**

- Nearly impenetrable barrier to air
  water penetration: Fusion welded 3 1/4" frame provide strength, stability, and rigidity
- More traditional wood appearance on exterior: Unique cove mold design
- Better thermal barrier than most other windows: .070" walls are a full 12% thicker than most other windows
- Lifetime warranty on all vinyl frames
- Design flexibility: Virtually any type of architectural window can be done

SPECIFICATIONS:	
Maximum Size	Non-Impact Fin: 71 ½" x 71 ½"
Maximum Size	Non-Impact Flange: 74 ½" x 72"
Maximize Size	Impact: 64" x 84"
Design Pressure	+/- 50-60 PSF
Glass	Insulated, Insulated Impact
Muntin	Grids Between Glass (GBG) or Simulated Divided Light (SDL)
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 1/4"
Colors	White, or Bronze Exterior / White Interior
Approvals/ Certifications	Earthwise, Good Housekeeping Seal, NFRC, Energy Star, Made in the USA Certified®, Florida State Product Approval











