

HORIZONTAL ROLLER & HORIZONTAL ROLLER P ALUMINUM IMPACT WINDOW

MAXIMUM STRENGTH, LONGER LIFE, & CORROSION RESISTANT

FEATURES & BENEFITS:

- **Superior Strength and Durability:** 3¼" frame depth
- **Maximize prevention of air and water penetration:** Double veined felts
- **Uniform external look throughout the building:** Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Protection against corrosion and longer life:** Stainless steel components
- **Ease-of-operation, install and longer life:** Heavy duty adjustable rollers
- **Easy Cleaning:** Removable operating sash



SPECIFICATIONS:

Maximum Size	Glazing	Nominal Glass	Design Pressure
74" x 72" XO or OX	Impact	5/16" Annealed	±60
74" x 72" XO or OX	Insulated Impact	5/8" IGU - 5/16" Ann	±60
72" x 60" XO or OX	Impact	7/16" Heat Strength	±80
74 1/8" x 63" XO or OX	Impact	1/2" Heat Strength	+100/-120
111" x 72" XOX equal	Insulated Impact	5/8" IGU - 5/16" Ann	±60
111" x 72" XOX unequal	Impact	5/16" Ann	±60
120" x 63" XOX*	Impact	1/2" Heat Strength	+100/-120

*Indicates high rise sill

ADDITIONAL SPECIFICATIONS:

Muntin	Flat, Profile
Grid Options	Colonial, Prairie, Perimeter, Other
Frame Depth	3 1/4"
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval

