

FWI 1000

SINGLE HUNG IMPACT ALUMINUM WINDOW

MAXIMIZE PROTECTION AGAINST WATER AND WIND-BORNE DEBRIS-
AT A GREAT VALUE



FEATURES & BENEFITS:

- **Superior Strength and Durability:**
3 ¼" frame depth
- **Maximize prevention of air and water penetration:**
Double veined felts
- **Uniform external look throughout the building:**
Uniform construction of all applications ensures windows with different DPs maintain the same external look
- **Protection against corrosion and longer life:**
Stainless steel components available
- **Ease-of-operation and longer life:**
Preloaded spring balancers
- **Enhanced energy efficiency:**
Insulated glass option available
- **Durable powder coated finish**

SPECIFICATIONS:

Maximum Size	Glazing	Nominal Glass	Design Pressure
53 ½" x 96"	Impact	5/16" Annealed	±60
53" x 77"	Impact	7/16" Heat Strength	+80/-100
53 ½" x 76.5" *	Impact	½" Heat Strength	+120/-150
48" x 72"	Insulated Impact	¾" IGU - 5/16" HS	±75
53 ½" x 78"	Insulated Impact	7/8" IGU - 7/16" HS	+80/-100

ADDITIONAL SPECIFICATIONS:

Muntin	Flat, Profile, GBG
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	3 ¼"
Colors	White, Bronze
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval

