



FiberTite Blue Roof Flashing Tape

Product Data

Seaman Corporation offers FiberTite Blue Roof Flashing Tape for sealing laps and penetrations of FiberTite Blue Roof temporary roof installations.

DESCRIPTION

FiberTite Blue Roof Flashing Tape is a self-adhered, waterproof flashing membrane that can be used for temporary seals when installing FiberTite Blue Roof Membrane. The product has an acrylic pressure sensitive adhesive that sticks well to the FiberTite Blue Roof material. The proprietary backing resists punctures and tears and conforms to various sealing needs during a temporary roof installation. The tape has a split paper release liner for easy and accurate positioning of the tape. See FiberTite Blue Roof details for examples of use.

INSTALLATION

To apply, peel back a few inches of one side of the split paper release liner to position the tape. Remove the liner while applying firm pressure to the flashing tape surface as it comes into contact with the Blue Roof Membrane. Repeat this procedure with the remaining side of the paper release liner and tape. Use a silicone roller to apply sufficient pressure along the entire tape surface to ensure a continuous seal and eliminate trapping air beneath the tape.

ENVIRONMENTAL CONDITIONS

FiberTite Blue Roof Flashing Tape may remain exposed to direct sunlight for up to 12 months.

PHYSICAL PROPERTIES

Backing	Proprietary Film
Adhesive	Acrylic
Liner	Heavy Paper, Split
Color	Tan
Roll Width	6-inches (101 mm)
Roll Length	75 feet (22.8 m)



For more information on FiberTite Systems and accessories please call: Seaman Corporation (800) 927-8578 International (330) 262-1111 www.fibertite.com

FiberTite® is a registered trademark of Seaman Corporation.

These specifications are current as of the date of printing. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data, visit:

www.FiberTite.com/document-library/product-data-sheets

