



FiberTite Gray Walkpad

Product Data

FiberTite walkway and protection materials are designed to improve slip resistance, promote positive traction and offer protection from potential damage caused by dropped tools or mishandled equipment.

DESCRIPTION

FiberTite Gray protection pads are manufactured from high grade vinyl and incorporate a deep herring bone ribbed embossed surface texture.

APPLICATION

Walkway and protection materials are used to provide defined paths to facilitate common rooftop traffic and traffic involved in regular servicing, maintenance and repairs. FiberTite walkway and protection materials are to be maintained in specific areas around roof access points (ladders, hatches, doorways, etc.), around mechanical equipment requiring periodic maintenance and as a walkway system on roof areas subject to frequent foot traffic.

Attach these pads by using hot-air to weld 6 in x 6 in (15 cm x 15 cm) strips of FiberTite membrane at the four corners on the back of the pads. Then “tack” weld the strips to the FiberTite Roofing System. Do not weld Gray protection pads directly to the roofing membrane.

For additional recommendations and requirements, please consult the most current versions of FiberTite Guide Specifications for the Installation of FiberTite Roofing Systems.

PHYSICAL PROPERTIES

Thickness	.25 in (0.6 cm)
Pad Size	2 ft x 4 ft (0.6 m x 1.2 m)
Dimensional Stability (%)	0.2
Elongation (%)	100%

These specifications are current as of the date of printing. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data, visit:

www.FiberTite.com/document-library/product-data-sheets



For more information on FiberTite Systems and accessories please call:
Seaman Corporation (800) 927-8578
International (330) 262-1111
www.fibertite.com

FiberTite® is a registered trademark of Seaman Corporation.

