


Category 6A Outdoor Cable

Need to support a Category 6A application in a wet environment? Hitachi Cable America (HCA) introduces our Category 6A outdoor cable. Made in the USA at our Manchester, New Hampshire facility, it is specifically designed to accommodate any and all Category 6A applications to the maximum distance permitted in the TIA Category 6A standard. From 10 gigabit Ethernet to HDBaseT to POE+, our Category 6A outdoor cable will support it.

As a manufacturer focused on maximizing physical and electrical performance, we don't cut corners when it comes to our cable designs. Our Category 6A outdoor cable features an inner core of four 23-gauge pairs separated by an electrical-enhancing shaped filler and flooded with water-blocking gel. This core, encapsulated by an inner jacket, is then wrapped in a polyester-backed aluminum foil. A rugged outer jacket is then applied to the construction with a layer of water-blocking aramid yarns impregnated with super absorbent polymer (SAP) beneath.

Whether this Category 6A cable is being installed in conduit or direct buried, it's more than up to the challenge. It's also available with a 20-year warranty. To learn more, contact your local Hitachi Cable America sales representative or contact HCA directly.




*Per NEC, cable must be terminated/transitioned within 50 ft. of entering building.

Made in USA

Category 6A Outdoor Cable

Product Highlights

REACH & RoHS compliant
Outside diameter (.360 inches/9.144 mm)
Tested from 1 to 660 MHz
Part Number: 30287-8
Suitable for direct burial, lashed aerial, duct and underground conduit applications
Cable core is filled with non-conductive, water-blocking gel
Rugged black polyolefin jacket
UV resistant jacket
Proven Shield Technology improves RFI and EMI performance.



Applications

10G BASE-T 10 Gigabit Ethernet (limited distance),
1000 BASE-T Gigabit Ethernet, 1000 Mbps ATM, 622 Mbps ATM
100 BASE-T Ethernet, Broadband Video, POE, POE+

Packaging

1,000 foot (305m) Reels

Temp Range

Storage Temperature: -40°C to +70°C (-40°F to +158°F)
Installation Temperature: -20°C to +70°C (-4°F to +158°F)
Operation Temperature: -40°C to +70°C (-40°F to +158°F)



Made in USA

Photo is for representation purposes only.

The products, their specifications, services and other information in this document are subject to change without notice.

HITACHI
Inspire the Next

 **Hitachi Cable America Inc.**

Hitachi Cable America Inc.
900 Holt Ave, Manchester, NH 03109 USA
+1.603.669.4347 Fax: +1.603.669.9621
www.hca.hitachi-cable.com

© 2014 Hitachi Cable America Inc. All rights reserved.