



NECAL Corporation

1326 South Water Street, Sparta, WI 54656
608.269.3000, www.necal.com

Technical Data Sheet

NECAL 8799-125 PRESSURE SENSITIVE ADHESIVE

DESCRIPTION

NECAL 8799-125 is a polyurethane foam supported pressure sensitive adhesive that exhibits very high performance.

FEATURES

NECAL 8799-125 is primarily intended for exterior use where extreme high performance is needed. An example is exterior automotive. NECAL 8799-125 has superior impact and vibration resistance.

PHYSICAL PROPERTIES

Composition:	Modified Acrylic (low surface energy)
Release Liner:	Available with P, W, H, J, VF, P1, or W1 liners
Thickness:	130 mils + or - 10%
Scrim:	Black Polyurethane closed cell foam
Adhesion:	120-150 oz. /in. (Aluminum/Polypropylene) 340-360 oz. /in. (Aluminum/Stainless)
Tensile: (2)	95 p.s.i., foam failure
Shear Adhesion: (3)	7 days +
Temperature Range:	Application: 50°F. Minimum Service: -40°F to 270°F

BONDING INSTRUCTIONS

Remove the release liner and apply to a clean, dry substrate. Use firm pressure to obtain maximum contact. Increasing application force will optimize bond strength to surface.

STORAGE DATA

The shelf life of this material is at least two years when stored in a cool, dry place.

NOTICE

The information shown here represents typical values, which may vary with each application. The values are not intended to be a performance guarantee. Users should determine, prior to use, the suitability of this material for their application.