



# NECAL Corporation

1326 South Water Street, Sparta, WI 54656  
608.269.3000, [www.necal.com](http://www.necal.com)

## Technical Data Sheet

### NECAL 8799-60 PRESSURE SENSITIVE ADHESIVE

#### DESCRIPTION

NECAL 8799-60 is a polyurethane foam supported pressure sensitive adhesive that exhibits very high performance.

#### FEATURES

NECAL 8799-60 is primarily intended for exterior use where extreme high performance is needed. An example is exterior automotive. NECAL 8799-60 has superior impact and vibration resistance.

#### PHYSICAL PROPERTIES

Composition:	Modified Acrylic (low surface energy)
Release Liner:	Available with P, W, H, J, VF, P1, H2 or W1 liners
Thickness:	65 mils + or - 10%
Scrim:	Black Polyurethane closed cell foam
Adhesion:	120-150 oz. /in. (Aluminum/Polypropylene) 340-360 oz. /in. (Aluminum/Stainless)
Tensile: (2)	95 p.s.i., foam failure
Shear Adhesion: (3)	7 days +
Temperature Range:	Application: 50°F. Minimum Service: -40°F to 270°F

#### BONDING INSTRUCTIONS

Remove the release liner and apply to a clean, dry substrate. Use firm pressure to obtain maximum contact. Increasing application force will optimize bond strength to surface.

#### STORAGE DATA

The shelf life of this material is at least two years when stored in a cool, dry place.

#### NOTICE

The information shown here represents typical values, which may vary with each application. The values are not intended to be a performance guarantee. Users should determine, prior to use, the suitability of this material for their application.