Product datasheet



UniFi AP Outdoor



Tanaza | Wi-Fi cloud management software

Technical product datasheet UniFi AP Outdoor



UniFi AP-Outdoor (UAP-Outdoor) Specifications		
Dimensions	17 x 8 x 3 cm	
Weight	0.5 kg without antennas 0.54 kg with antennas (2)	
Ports	Ethernet (2) (Auto MDX, autosensing 10/100 Mbps)	
Buttons	Reset	
Antennas	(2) External 6 dBi omni antenna included 191 mm (Length), 13mm (Diameter)	
Wi-Fi Standards	802.11 b/g/n*	
Power Method	Passive Power over Ethernet (12-24V)	
Power Supply	24V 1A PoE Adapter included	
Maximum Power Consumption	4.6 Watts	
Max TX Power	27 dBm	
BSSID	Up to four per radio	
Power Save	Supported	
Wireless Security	WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i	
Certifications	CE, FCC, IC	
Mounting	Wall/Ceiling (Kits included)	
Operating Temperature	-30 to 75°C (-22 to 167° F)	
Operating Humidity	5 - 95% Condensing	
	Advanced Traffic Management	
VLAN	802.1Q	
Advanced QoS	Per-user rate limiting	
Guest traffic isolation	Supported	
WMM	Voice, video, best effort, and background	

100+

Supported Data Rates (Mbps)	
Frequency (MHz)	
802.11n	MCS0 - MCS15 (6.5 Mbps to 300 Mbps), HT 20/40
802.11b	1, 2, 5.5, 11
802.11g	6, 9, 12, 18, 24, 36, 48, 54

* 2.4GHz

Concurrent Clients

