



CURTAINSIDE

Two-Sided - One-Sided - Custom



Open the Possibilities

Increase your productivity with a Marion Curtainside. Quick & easy access to three sides is a time and money saving feature.

“Designed and built as a curtainside... not a flatbed conversion.”



Removable Support Poles

Full forklift access entry made easy with no loss of integrity.



VERSATILITY & STRENGTH

Built solid from the floor up.

Design your truck for a dual purpose and add graphics to your curtain to create a moving billboard. Curtains are PVC coated polyester material.

A variety of curtain colors are available at



no additional charge. Quik release latches are located at the rear of the body; ratchet

tensioners at the front corners provide tension horizontally to reduce curtain flutter while driving.



Available Lengths: 10' to 30'
Available Heights: 79-1/8" to 109-1/8"
Custom Sizes Available

OPTIONS

Customize your body to your needs.

- | | |
|---------------|--------------------------------|
| Insulation | Scuff Plates |
| Aluminum Roof | Liftgates |
| Walk Ramps | Platform Extensions |
| Side Doors | Interior Cargo Control Options |



Floor	<ul style="list-style-type: none"> 4" structural channel stringers 4" 80,000 psi I-beam crossmembers on 12" centers Two (2) additional crossmembers at rear of van 1-1/8" laminated hardwood floor, two screw per board, per crossmember Undercoated
Front/Side Walls	<ul style="list-style-type: none"> Front corner posts and front top rail constructed of 10 ga. steel Upper side rails/curtain tracks are extruded aluminum Marker lights with standard lenses Reflectors per FMVSS 5/8" core, color impregnated white FRP front wall panel
Rear Frame/Door	<ul style="list-style-type: none"> 7 ga. steel outer posts, inner reinforcements, and smooth steel rear threshold Full width eave trough above rear door that also provides recessed protection for the rear marker lights 13" chrome access handle located at curbside rear Upgraded Todco rollup rear door - 3/4" plastic - including top, bottom & side seals, and 30" pull strap 4-1/4" smooth steel level entry with recessed drain trough - flooring end cap routed flush with top of floor. Paint rear door polyurethane white
Roof	<ul style="list-style-type: none"> Upper side rails/curtain tracks are extruded aluminum Crowned rolled galvanized steel hat section rafters on 24" centers .06" one piece translucent roof
Mounting	<ul style="list-style-type: none"> Mounted including frame wood, U bolts, mud flaps and DOT step
Paint	<ul style="list-style-type: none"> All steel parts painted polyurethane - silver gray Upper side rail/curtain track extrusions natural aluminum Curtain valances grey Front FRP panel, rear door (swing or roll-up) and curtains white
Curtains	<ul style="list-style-type: none"> Curtains are PVC coated polyester material Curtains include vertical and horizontal nylon reinforcement webbing to add strength and serve as a rip stop for security Curtains are captive to the top rail and tensioned vertically with nylon belts and buckles that are spaced on 24" centers. Horizontal tensioning is achieved with a ratchet "tensioner" device at the front of each side of the van. A "quick release" is included at the rear of each side of the van One removable support on each side. Two supports on each side on 26' + vans Standard curtain color is white

Certified to ISO 9001

Marion Body Works, Inc. • Marion, WI
 Phone: 715-754-5261 • www.marionbody.com