



DRY VANS

Aluminum/Smoothside-FRP-Insulated



Dry Vans, Freight Bodies, Box Trucks...

It doesn't matter what you call it...we build what you need to deliver your product! That's what we do and we have been doing it since 1905.

*“ Built tough to last,
built smart to create value. ”*



DURABILITY & STRENGTH

Strong rear frame and durable flooring.

Our rugged 7 gauge smooth steel rear threshold is 25% thicker than the competitors 10 gauge, providing superior strength and a better door seal to protect your cargo. Full width drain trough to help keep the floor dry for longer life and safety. Steel fasteners are cadmium plated for superior corrosion resistance.



OPTIONS

Customize your body to your needs.

- Insulation
- Aluminum Roof
- Walk Ramps
- Side Doors
- Scuff Plates
- Liftgates
- Stainless Steel
- Platform Extensions
- Rubber Dock Bumpers
- Interior Cargo Control options



FEATURES

Floor	<ul style="list-style-type: none"> • 4" I beam stringers • 3" 60,000 psi I-beam crossmembers on 12" centers • 1-1/8" laminated hardwood floor - two 5/16" screws per board (staggered pattern), per crossmember • Undercoated
Front/Side Walls	<ul style="list-style-type: none"> • Aerodynamic extruded aluminum 5" radius front corner posts and front top radius • Extruded aluminum lower front rail, lower and upper side rails • Marker lights with standard lenses • Reflectors per FMVSS <p>Aluminum</p> <ul style="list-style-type: none"> • Full width x 8" high steel reinforcement angle at base of front wall • Seven (7) posts on front wall • Galvanized steel "Z" section side wall posts on 16" centers • .040" prepainted white aluminum exterior panels. "Smooth Side" construction - exterior surface of side and front wall panels are rivet-free <p>FRP</p> <ul style="list-style-type: none"> • 5/8" core color impregnated white FRP exterior panels
Rear Frame/Door	<ul style="list-style-type: none"> • Rear corner posts and door frame formed of galvanized steel • 13" chrome access handle located at curbside rear • Roll-up rear door, 94" wide opening with top, bottom and side seals. Includes 30" pull strap • 4-1/4" smooth steel level entry with recessed drain trough - flooring end cap routed flush with top of floor
Roof	<ul style="list-style-type: none"> • Aerodynamic cast aluminum front corner caps with gusseted design • Crowned rolled galvanized steel hat section rafters on 24" centers • .06" one piece translucent roof
Mounting	<ul style="list-style-type: none"> • Mounted including frame wood, U bolts, mud flaps and DOT step

Available Lengths: 10' to 30'
Available Heights: 79-1/8" to 109-1/8"
Custom Sizes Available



Certified to ISO 9001

Marion Body Works, Inc. • Marion, WI
 Phone: 715-754-5261 • www.marionbody.com