



MIRACLE BOND

Non-Sag Fast Cure Epoxy

MIRACLE BOND is a two component, 100% solids, high aspect ceramic-blend epoxy. It is a solvent free, high modulus, moisture insensitive, non-sag epoxy system. MIRACLE BOND is ideal for: bonding almost any material together, repairing holes, spalls, and cracks in concrete, repairing rotted wood, install & repair anchor bolts, or hand rails, and as a high strength structural adhesive. MIRACLE BOND can be used in concrete, hollow block, brick, stone & wood. It is ideal for use in a wide range of temperatures from 40° F. to 110° F. MIRACLE BOND is an excellent choice where a **high strength** adhesive **with maximum field reliability** is desired.

USES & ADVANTAGES:

Bonding Agent (metal, concrete, brick, wood, stone block)
Excellent spall patching material
Perfect for horizontal, overhead and screen application: Non-Sag /No Drip
Crack injection sealer around ports & cracks
Moisture insensitive
For indoor & outdoor use
Will not soften over time

CLASSIFICATION:

Professional contractor grade epoxy adhesive for anchoring and concrete repair

Packaging: 9 oz. EZ-Mix cartridge

How to use: Single cartridge use: Use standard 10 oz. caulking gun. Follow complete manufacturers details. (Mix Ratio: A: B Volume 1:1)

Color: Concrete Gray

Compressive Yield Strength – 7 Days – 9,800 psi

Gel Time (100 gram mass @ 78° F. – 8 minutes

SURFACE PREPARATION: Surfaces must be free from oil, grease or any loose debris, such as dirt, dust, gravel, etc. Crack should be cleaned with a wire brush, compressed air or degreaser. If water/degreaser is used; the area should be allowed to dry, for best results.

WORKING TIME – 20 MINUTES CURE TIME, when substrate is at least 75° F = 2 Hours

3 Chattanooga ♦ Irvine, California ♦ 92620 ♦ Phone: 714-832-8441

E-mail: info@chemexindustries.com ♦ www.chemexindustries.com

T
E
C
H
N
I
C
A
L

R
E
P
O
R
T

