Report Number: 346





RUST CONVERTER

Halts rust and prevents future corrosion

This liquid surface conditioner and primer changes existing rust into a dark, inert protective polymeric coating that seals out moisture and prevents future rust and corrosion. It also provides an excellent primer coating on rusty steel and iron for the application of oil-based paints. Once painted, it helps surfaces resist the effects of the weather without peeling or cracking.

Protects against:

Sector Sector

Rain
Sun
Salt spray
Salt spra

Product # 346

Features and Benefits

- Converts rust into a durable, long-lasting, protective coating.
- Prepares metal surfaces to readily accept final coats of paint.
- ③ No sandblasting, grinding or etching required.

Directions Complete directions on product label

Apply two coats allowing at least 20 minutes drying time between coats. Allow 48 hours of cure time before applying an oil-based paint.

One gallon will cover 500 square feet of a smooth nonporous surface. Irregular, porous surfaces will require more product.

Safety

Caution: Harmful if swallowed. Eye: irritant. Keep out of the reach of children.

Properties

| Appearance | Opaque beige liquid |
|------------------|---|
| Fragrance | |
| Ready-to-use | Yes |
| Specific gravity | 1.13 |
| pH | . 3.0-4.0 |
| Application | . Use brush or roller |
| Protect from | . Freezing temperatures or temperature above 100 °F |



3 Chattanooga ♦ Irvine, California ♦ 92620 ♦ Phone: 714-832-8441 E-mail: info@chemexindustries.com ♦ www.chemexindustries.com