

# Micro Perf, Cut & Crease Multi-Tool Combo

Includes Complete Multi-Tool & Fast Fit Creasing to fit 36mm exit shaft

Stock Code: MT-01/COMBO



Contents of Combo Kit



Perforating Parts



Cutting Parts



Creasing Cassette Parts

## Contents of Package

- 1 x Male Blade Holder (MT-BH-01/36):**  
used to hold the perforating blade whilst material is fed through
- 2 x Black Gripper Band (M-15):**  
used to feed and support material through device
- 1 x Extraction Tool:**  
used to change rubber grippers and creasing ribs from Male Blade Holder

## Perforating Components

- 2 x Female Nylon Sleeve Holders (CP-AP-NSH/36):**  
used to secure nylon during perforating and kiss-cutting process
- 1 x Black Nylon Sleeve (CP-NY/SL-36):**  
used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto nylon sleeve (for perforating and kiss-cutting only)
- 1 x Blue Nylon Sleeve (CP-NY/SL-36-B):**  
used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto nylon sleeve

## Perforating Blades:

- 17 TPI (MPB-17) (250/280-350gsm)
- Blue Nylon Sleeve
- 17 TPI (MPB-17) (170-250/280gsm)
- Black Nylon Sleeve
- 25 TPI (MPB-25) (100-170gsm)
- Black Nylon Sleeve
- 52 TPI (MPB-52) (65-100gsm)
- Black Nylon Sleeve

- 8 TPI (MPB-8) (optional)
- 12 TPI (MPB-12) (optional)
- 40 TPI (MPB-40) (optional)
- 72 TPI (MPB-72) (optional)

## Cutting Components

- 2 x Cutting Bosses (CB-01):**  
used to aid cutting, producing scissor effect as material is fed through device (for slitting only)
- 2 x Cutting Knives (CK-01):**  
(62.50mm Outer Diameter) used for trimming on normal stock
- Kiss-Cutting Blade (CK-02):**  
(58.35mm Outer Diameter **optional**) used for kiss-cutting applications
- Long Cutting Knives (CK-03):**  
(64mm Outer Diameter **optional**) used for trimming on heavy stock

- 2 x Blue Gripper Band (M-40):**  
used to feed and support material through device during edge trimming only

- 1 x Waste Stripper (TWS-ID/AGOR-5):**  
acts as waste deflector preventing waste material wrapping around machine shaft; width options include:  
5mm Width (TWS-ID/AGOR-5)  
4mm Width (TWS-ID/AGOR-4) **optional**  
3mm Width (TWS-ID/AGOR-3) **optional**

## Creasing Components

- 1 x Male Creasing Component (M):**  
contains the split gripper crease ribs
- 1 x Female Creasing Component (F):**  
(with bearing) contains grooves in which material is pressed
- 2 x Orange Gripper Crease (M-66):**  
used to crease material weight between 100-200gsm
- 2 x Blue Gripper Crease (M-65):**  
used to crease material weight between 200-270gsm
- 2 x Yellow Gripper Crease (M-64):**  
used to crease material weight between 250-350gsm

Shaft Size: 36mm Exit Shaft  
Outer Diameter: 58mm

## Additional Information

To add the creasing cassette simply remove the largest black spacer on the blade holder and slide on the creasing rib cassette.

The creasing unit is supplied with a bearing female.

You can crease and perforate as close as 5mm.



Crease & Perf



Crease & Cut



Tech 114 (Blade Holder) and 261 (Nylon Sleeve Holder) Tech 304 (creasing bearing female)