

CP-Applicator

to fit 35mm exit shaft

Stock Code: **CP-AP-SM/35-FP**

Shaft Size: **35mm Exit Shaft**
Outer Diameter: **58mm**

SETTINGS



1x **Orange** Female Component

used to crease light material (100-150gsm)

1x **Blue** Female Component

used to crease medium material (150-220gsm)

1x **Yellow** Female Component

used to crease heavy material (220-350gsm)

Perforating Blades:

17 TPI (**MPB-17**) (250/280-350gsm)

Blue Nylon Anvil

17 TPI (**MPB-17**) (170-250/280gsm)

Black Nylon Anvil

25 TPI (**MPB-25**) (100-170gsm)

Black Nylon Anvil

52 TPI (**MPB-52**) (65-100gsm)

Black Nylon Anvil

8 TPI (**MPB-8**) (optional)

12 TPI (**MPB-12**) (optional)

40 TPI (**MPB-40**) (optional)

72 TPI (**MPB-72**) (optional)

2x **Black** Gripper Bands (**M-15**):

used to feed and support material through device

2x **Orange** Creasing Ribs (**M-29**):

used to feed and support material through device

2x **Blue** Creasing Ribs (**M-17**):

used to feed and support material through device

2x **Yellow** Creasing Ribs (**M-16**):

used to feed and support material through device

2x **Perforator** Blade Seals (**M-10**):

used to feed and support material through device

1x **Extraction** Tool

used to remove gripper crease from gripper crease holder

Contents of Package

Compatible on:

Machines with widths between 56-80cm

1x **Male** Blade Holder

used to hold the perforating blade and gripper holder whilst material is fed through

2x **Female** Nylon Anvil Holders

used to secure nylon during perforating process

2x **Black** Nylon Anvil (**CP-NY/SL-35**):

used on light /medium weight stocks (65-250/ 280gsm), to allow sufficient blade pressure onto material during perforating process

2x **Blue** Nylon Anvil (**CP-NY/SL-35-B**):

used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

1x **Gripper** Crease Holder

used to hold gripper crease into position during creasing process

1x **Spacer**

used to replace gripper crease holder during perforating process



Tech 078