

# Micro Perf, Cut & Crease Multi-Tool Combo

Includes Complete Multi-Tool & Fast Fit Creasing to fit 35mm exit shaft

Stock Code: **MT-02/COMBO-01**

## Contents of Package



Contents of Combo Kit



Perforating Parts



Cutting Parts



Creasing Cassette Parts  
Fixed Female shown at right

**1 x Male Blade Holder (MT-BH-02/35):**  
used to hold the perforating blade whilst material is fed through

**2 x Black Gripper Band (M-15):**  
used to feed and support material through device

**1 x Extraction Tool:**  
used to change rubber grippers and creasing ribs from Male Blade Holder

### Perforating Components

**2 x Female Nylon Sleeve Holders (CP-AP-NSH/35):**  
used to secure nylon during perforating and kiss-cutting process

**1 x Black Nylon Sleeve (CP-NY/SL-35):**  
used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto nylon sleeve (for perforating and kiss-cutting only)

**1 x Blue Nylon Sleeve (CP-NY/SL-35-B):**  
used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto nylon sleeve

### Perforating Blades:

17 TPI (**MPB-17**) (250/280-350gsm)  
Blue Nylon Sleeve  
17 TPI (**MPB-17**) (170-250/280gsm)  
Black Nylon Sleeve  
25 TPI (**MPB-25**) (100-170gsm)  
Black Nylon Sleeve  
52 TPI (**MPB-52**) (65-100gsm)  
Black Nylon Sleeve

8 TPI (**MPB-8**) (optional)  
12 TPI (**MPB-12**) (optional)  
40 TPI (**MPB-40**) (optional)  
72 TPI (**MPB-72**) (optional)

### Cutting Components

**2 x Cutting Bosses (CB-02):**  
used to aid cutting, producing scissor effect as material is fed through device (for slitting only)

**2 x Cutting Knives (CK-01):**  
(62.50mm Outer Diameter) used for trimming on normal stock

**Kiss-Cutting Blade (CK-02):**  
(58.35mm Outer Diameter **optional**) used for kiss-cutting applications

**Long Cutting Knives (CK-03):**  
(64mm Outer Diameter **optional**) used for trimming on heavy stock

**2 x Blue Gripper Band (M-40):**  
used to feed and support material through device during edge trimming only

**1 x Waste Stripper (TWS-ID/35-5):**  
acts as waste deflector preventing waste material wrapping around machine shaft; width options include:  
5mm Width (**TWS-ID/35-5**)  
4mm Width (**TWS-ID/35-4**) **optional**  
3mm Width (**TWS-ID/35-3**) **optional**

### Creasing Components

**1 x Male Creasing Component (M):**  
contains the split gripper crease ribs

**1 x Female Creasing Component (F):**  
(with fixed female or bearing) contains grooves in which material is pressed

**2 x Orange Gripper Crease (M-163):**  
used to crease material weight between 100-200gsm

**2 x Blue Gripper Crease (M-162):**  
used to crease material weight between 200-270gsm

**2 x Yellow Gripper Crease (M-161):**  
used to crease material weight between 250-350gsm

Shaft Size: **35mm Exit Shaft**  
Outer Diameter: **58mm**

### Additional Information


This Device will fit machines with widths between 56-80cm

To add the creasing cassette simply remove the largest black spacer on the blade holder and slide on the creasing rib cassette.

The creasing unit is supplied with either a fixed female or a bearing female.



Crease & Perf



Crease & Cut



Tech 111 (Blade Holder) and 271 (Nylon Sleeve Holder) Tech 354 (creasing bearing female)