

Micro Perf, Cut & Crease Multi-Tool Combo

Includes Complete Multi-Tool & Fast Fit Creasing to fit 35mm exit shaft

Stock Code: **MT-02/COMBO**



Contents of Combo Kit



Perforating Parts



Cutting Parts



Creasing Cassette Parts
Fixed Female shown at right

Contents of Package

- 1 x Male Blade Holder (MT-BH-02/35):**
used to hold the perforating blade whilst material is fed through
- 2 x Black Gripper Band (M-15):**
used to feed and support material through device
- 1 x Extraction Tool:**
used to change rubber grippers and creasing ribs from Male Blade Holder

Perforating Components

- 2 x Female Nylon Sleeve Holders (CP-AP-NSH/35):**
used to secure nylon during perforating and kiss-cutting process
- 1 x Black Nylon Sleeve (CP-NY/SL-35):**
used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto nylon sleeve (for perforating and kiss-cutting only)
- 1 x Blue Nylon Sleeve (CP-NY/SL-35-B):**
used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto nylon sleeve

Perforating Blades:

- 17 TPI (**MPB-17**) (250/280-350gsm)
Blue Nylon Sleeve
- 17 TPI (**MPB-17**) (170-250/280gsm)
Black Nylon Sleeve
- 25 TPI (**MPB-25**) (100-170gsm)
Black Nylon Sleeve
- 52 TPI (**MPB-52**) (65-100gsm)
Black Nylon Sleeve
- 8 TPI (**MPB-8**) (optional)
- 12 TPI (**MPB-12**) (optional)
- 40 TPI (**MPB-40**) (optional)
- 72 TPI (**MPB-72**) (optional)

Cutting Components

- 2 x Cutting Bosses (CB-02):**
used to aid cutting, producing scissor effect as material is fed through device (for slitting only)
- 2 x Cutting Knives (CK-01):**
(62.50mm Outer Diameter) used for trimming on normal stock
- Kiss-Cutting Blade (CK-02):**
(58.35mm Outer Diameter **optional**) used for kiss-cutting applications

Long Cutting Knives (CK-03):
(64mm Outer Diameter **optional**) used for trimming on heavy stock

2 x Blue Gripper Band (M-40):
used to feed and support material through device during edge trimming only

1 x Waste Stripper (TWS-ID/35-5):
acts as waste deflector preventing waste material wrapping around machine shaft; width options include:
5mm Width (**TWS-ID/35-5**)
4mm Width (**TWS-ID/35-4**) **optional**
3mm Width (**TWS-ID/35-3**) **optional**

Creasing Components

- 1 x Male Creasing Component (M):**
contains the split gripper crease ribs
- 1 x Female Creasing Component (F):**
(with fixed female or bearing) contains grooves in which material is pressed
- 2 x Orange Gripper Crease (M-66):**
used to crease material weight between 100-200gsm
- 2 x Blue Gripper Crease (M-65):**
used to crease material weight between 200-270gsm
- 2 x Yellow Gripper Crease (M-64):**
used to crease material weight between 250-350gsm

Shaft Size: **35mm Exit Shaft**
Outer Diameter: **58mm**

Additional Information

This Device will fit machines with widths between 56-80cm

To add the creasing cassette simply remove the largest black spacer on the blade holder and slide on the creasing rib cassette.

The creasing unit is supplied with either a fixed female or a bearing female



Crease & Perf



Crease & Cut



Tech 111 (Blade Holder) and 271 (Nylon Sleeve Holder) Tech 258 (creasing bearing female)