Multi-Tool

to fit 28.87mm exit shaft (Full Pack; options 1 - 2)

Stock Code: MT-BF/28

SETTINGS



Additional Information

Compatible on:

Contents of Package

1x Male Blade Holder (MT-BH-BF/28):

used to hold the perforating blade whilst material is fed through

2x Female Nylon Sleeve Holders (CP-AP-NSH-BF/28):

used to secure nylon during perforating and kisscutting process

1x Black Nylon Sleeve (CP-NY/SL-BF-28):

used on light weight stocks (65-250/280gsm), allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

1x Blue Nylon Sleeve (CP-NY/SL-BF-28-B):

used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

2 x Cutting Bosses (CB-BF/28-01):

used to aid cutting, producing scissor effect as material is fed through device (for slitting only)

Shaft Size: 28.58mm / 11/8" Outer Diameter: 55.87mm / 2 1/5"

2 x Cutting Knives (CK-BF/28-01):

(60.15mm Outer Diameter) used for trimming on normal stock

Long Cutting Knives (CK-BF/22-03):

(61.65mm Outer Diameter **optional**) used for trimming on heavy stock

2 x Black Gripper Band (M-80): used to feed and support material through device

2 x Blue Gripper Band (M-149):

used to feed and support material through device during edge trimming only

Perforating Blades:

17 TPI (MPB-17/BF/28mm) (250/280-350gsm) Blue Nylon Sleeve

17 TPI **(MPB-/BF28/17mm)** (170-250/280gsm) Black Nylon Sleeve 25 TPI **(MPB-25/BF/28mm)** (100-170gsm) Black Nylon Sleeve 52 TPI **(MPB-52/BF/28mm)** (65-100gsm) Black Nylon Sleeve

1 x Waste Stripper (TWS-ID/MBO 30-5):

acts as waste deflector preventing waste material wrapping around machine shaft; width options include: 5mm Width (TWS-ID/MBO 30-5) 4mm Width (TWS-ID/MBO 30-4) optional 3mm Width (TWS-ID/MBO 30-3) optional

1 x Extraction Tool:

used to change rubber grippers from Male Blade Holder



Tech 229 (Blade Holder) and 230 (Nylon Sleeve Holder)

www.technifoldusa.com Tel: 973-383-7920