



FS-2020D

Black & White Printing Solution

## ECONOMICAL. ECOLOGICAL. ECOSYS PRINTERS.

- Fast output speed of 37 pages per minute
- ECOSYS<sup>®</sup> long life consumables reduce operating costs
- Maximum 1,100 sheet paper capacity
- Unique KX print driver and optional network interface card
- Productive duplex function saves paper
- Ultra-reliable technology





**Basic Specifications** 

**FS-2020D** 



FS-2020D with standard configuration 15.04"W x 15.51"D x 11.22"H



FS-2020D with additional paper feeder 15.04"W x 15.51"D x 15.55"H



Easy-to-replace toner container



Front facing USB host interface supports PDF and **TIFF** file formats

| Basic Specifications  |  |
|---|--|
| Technology and Configuration  | Kyocera ECOSYS® Black & White Network Printer  |
| Pages Per Minute  | Letter: 37, Legal: 28, A4: 35  |
| Warm Up Time  | 17 seconds or less from main power on, 15.5 seconds or less from sleep mode  |
| First Print Out Time  | 9 seconds or less (EcoFuser off)   |
| Resolution  | Fine 1200 Mode (1,200 x 1,200 dpi), Fast 1200 Mode (1,800 x 600 dpi), 600 x 600 dpi, 300 x 300 dpi   |
| Memory  | Standard 128MB, upgradable to 1152MB via 144 pin DDR2 DIMMs; Standard CF Card Slot (type 1)  |
| Hard Disk Drive   | Optional HD-5A   |
| Duplex Printing   | Standard Duplex, 18.5 Pages Per Minute Letter  |
| Electrical Requirements   | 120V, 50/60Hz, 7.6A; 220 to 240 VAC, 50/60Hz, 4.3A   |
| Dimensions / Weight   | 15.04"W x 15.51"D x 11.22"H / 35.7 lbs   |
| Typical Energy Consumption (TEC)  | 3.103 kWh/week (120V)  |
| Noise (ISO 7779 / ISO 9296)1  | Printing 52dB(A), Ready 29dB(A)  |
| Manufacturing Standards   | This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental<br>impact standard  |
| Maximum Monthly Duty Cycle  | 150,000 Pages Per Month  |
| Recommended Monthly Volume  | 1,000 to 20,000 Pages Per Month  |
| Controller Specifications   |  |
| CPU / MHz   | Embedded Power PC 440 / 533 MHz  |
| PDL / Emulations  | PRESCRIBE, PCL6 (PCL5c, PCLXL), KPDL (PS3), XPS <sup>2</sup>   |
| Direct Print  | PDF 1.5 Direct Print   |
| Fonts   | 93 Scalable Fonts for PCL/Postscript, 8 Fonts for Windows Vista, 1 Bitmap Font   |
| Barcodes  | 45 Barcodes (EAN8, EAN13, EAN128), and support for two dimensional Barcodes (PDF-417)  |
| Supported Client Operating Systems  | Certified for Microsoft® Windows Vista® 32/64-bit, Windows® 2000, Windows XP® 32/62-bit,   |
|   | Windows Server 2003 32/64-bit, Windows Server 2008 32/64-bit, Mac OS X v10.39, v10.4, v10.5; Linux   |
| Supported Network Operating Systems <sup>3</sup>                            | Microsoft Windows 2000, Server 2003, XP, Vista, 2003 64-bit, XP 64-bit, (for Microsoft IPv6 compatible wit<br>Windows 2003, XP, and Vista); Novell 5.1 and Later; Mac OS X 10.2.8, v10.3, v10.4, v10.5; Linux, Unix  |
| Printer Management  | Status Monitor, Command Center Web Interface, PrintQ Manager, KMnet Viewer, KMnet Admin, KMnet for Accounting  |
| Connectivity / Interfaces   | High Speed USB 2.0 Host, Parallel IEEE1284 Interface, CF-1 Card type 1, KUIO/W (1 slot)  |
| Network Protocols <sup>3</sup>  | IPv6: HTTP, LPD, FTP, IPP, RawPort, ICMPv6, LLTD, SNTP, DHCPv6, SMTP, POP3, DNS, SNMPv1/v2c/v3, WSL<br>IPv4: HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMP, DHCP, SMTP, POP3, SNTP, DNS, WINS, NetBIOS ove<br>TCP/IP, SNMPv1/v2c/v3, Apple Bonjour Compatible, IPPS, LLTD, WSD<br>IPX/SPX, NetWare (NDS/Bindery), AppleTalk, NetBEUI |
| Security  | IPsec, 802.1x, SSL/TLS (HTTPS, IPPS), SNMPv3, EAP-TLS, PEAP, AH, ESP   |
| Drivers   | KX Driver For Windows®, PPD for Mac, PPD for Linux/UNIX, Mini Driver, Windows® 64 Bit Drivers  |
| Departmental Accounting   | 100 Department Codes   |
| Additional Print Features   | LCD Operation Panel, N-Up Printing, Private Print, Virtual Mailbox, Document Storage, EcoPrint Mode,<br>Poster Mode, Internet Printing IPP 1.0   |
| Multi Language Support  | English, Italian, French, Spanish, German, Portuguese, Dutch, Russian  |
| Paper Supply  |  |
| Standard Paper Sources  | 500 Sheet Drawer, 100 Sheet Multi-Purpose Tray   |
| Standard / Maximum Paper Sources  | 2 / 3 including Multi-Purpose Tray   |
| Standard Paper Drawer Size / Weight   | Letter, Legal, Oficio2, A4, A5, B5, A6R, Executive, 16 kai, Folio, Custom 5.47" x 8.27" / 16-32 lb Bond  |
| Standard Duplex Paper Size / Weight   | Letter, Legal, A4, A5, B5, Folio / 16-32 lb Bond   |
| Standard / Maximum Paper Capacity   | 600 / 1.100 Sheets   |
| Multi-Purpose Tray Paper Size / Weight                                      | Letter, Legal, A4, B5, A5, Folio, Oficio 2, Statement, Executive, A6, B6, B5, Envelope, Monarch, DL;<br>Custom 2.76" x 5.83" to 8.5" x 14" / 16 lb Bond - 120 lb Index   |
| Input Materials   | Plain, Preprinted, Bond, Recycled, Rough, Letterhead, Color, Pre-Punched, High Quality, Transparency,<br>Labels, Bond, Vellum, Envelope, Cardstock, Thick Paper, Custom  |
| Output Capacity   | 250 Sheets   |
| Paper Handling Options  |  |
| PF-310 Paper Feeder <sup>4</sup>  |  |
| Paper Capacity  | 500 Sheets   |
| Paper Size / Weight   | 8.5" x 11", 8.5" x 14", Oficio2, A4, A5R, B5, Folio / 16-32 lb Bond  |
| Dimensions / Weight   | 15.04"W x 15.51"D x 4.33"H / 8.6 lbs   |
| Consumables   |  |
| ourisuriance  | TK-342 Toner for 12,000 pages⁵ (ships with 6,000 pages)  |
| Black Toner   |  |
|   |  |
| Additional Options  |  |
| Black Toner<br>Additional Options<br>Additional Memory<br>Network Interface | 144 pin 64, 128, 256, 512 or 1024MB DDR2 SDRAM DIMMS<br>Optional IB-31 Network Interface Supports Security and Compliance <sup>6</sup>   |

May require software from the NOS vendor or third-party vendor
The FS-2020D can be configured with up to 1 additional PF-310 Paper Feeder

In accordance with ISO19752
The FS-2020D can be configured with the optional IB-31 NIC or optional HD-5A HDD, but not concurrently

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted - and reducing landfill waste.

ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today. Visit our TCO Tracker at www.kyoceramita.com and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA © 2009 Kyocera Mita America, Inc. IC# 855D400197

