



**FS-1135MFP**

**Black & White Multifunctional Printer**

**ECONOMICAL. ECOLOGICAL. ECOSYS TECHNOLOGY.**

- Fast output speed of 37 pages per minute
- Standard print, copy, fax, and color scan
- Standard duplex and 300 sheet paper capacity
- USB host interface for convenient print-from and scan-to functionality
- LED illumination source
- RAM-based Private Print capabilities
- ECOSYS® long life consumables reduce operating costs
- Kyocera ultra-reliable technology





# FS-1135MFP



FS-1135MFP shown with standard configuration  
19.4" W x 16.9" D x 17.6" H



FS-1135MFP shown with 2 optional (PF-120) paper drawers  
19.4" W x 16.9" D x 25.4" H



Easy-to-replace toner container

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today.

### Basic Specifications

Configuration	Black & White Multifunctional Printer - Standard Copy, Print, Fax, and Color Scan
Pages Per Minute	Letter: 37 ppm; Legal: 30 ppm; A4: 35 ppm; Duplex: 20 ppm (Letter)
Warm-up Time	20 Seconds or Less
First Copy / Print Out Time	6.9 Seconds / 7.0 Seconds
Resolution	1200 x 1200 dpi, 1800 x 600 dpi (Fast 1200 Mode), 600 x 600 dpi, 300 x 300 dpi
Memory (Standard / Maximum)	256 MB / 768 MB
Duplex	Standard Stackless
Electrical Requirements	120V, 60Hz, 10.0A or more; 220-240V, 50/60Hz, 6.0A
Dimensions / Weight	19.4" W x 16.9" D x 17.6" H / 40.0 lbs (standard configuration)
TEC	3,600 Wh/week
Maximum Monthly Duty Cycle	20,000 Pages Per Month

### Paper Supply

Standard Paper Sources	Standard 250 Sheet Paper Drawer, 50 Sheet Multi Purpose Tray
Optional Paper Sources	Up to two (2) optional 250 Sheet Paper Drawers (PF-120) can be added
Paper Capacity	Standard: 300 Sheets; Maximum: 800 Sheets
Paper Size	4.1" x 5.8" - 8.5" x 14" via Drawers, 2.8" x 5.8" - 8.5" x 14" via MPT
Paper Weight	Drawers: 16 - 32 lb Bond (60 - 120gsm); MPT: 16 lb Bond - 120 lb Index (60 - 220gsm)
Input Materials	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes (MPT only)

### Document Processor

Type / Capacity	Standard Reversing Automatic Document Processor / 50 Sheets (Letter)
Copy Scan Speed	35 ipm
Acceptable Originals / Weights	Letter, Legal, A4 / Simplex: 13 - 32 lb Bond (50 - 120gsm), Duplex 13 - 29 lb Bond (50 - 110gsm)

### Duplex

Paper Size	Letter, Legal, A4
Paper Weight	16 - 28 lb Bond (60 - 105gsm)
Duplex Modes	1:2; 2:2; 2:1

### Copy Specifications

Image Mode	Text, Photo, Text/Photo
Continuous Copy	Yes 1 - 999 / Auto Reset to 1
Additional Copy Features	Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Priority Copy, Job Programs
Magnification / Zoom	Full Size, 7 Reduction, 5 Enlargement Preset Ratios, 25 - 400% in 1% step increments
Document Box	Job Box for RAM Based Private Print, Removable Memory for Print-From / Scan-To USB

### Printer Specifications

Controller	PowerPC 440 / 667MHz
PDLs / Emulations	PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS, PDF 1.5, IBM ProPrinter X24E, Epson LQ-850, Diablo 630, Line Printer
Fonts	101 KPDL3, 93 PCL6, 8 Vista, 1 Bitmap, 45 Barcodes, 1 PDF 417
Windows OS Compatibility	Windows XP / 2003 / Vista / 2008 / 7
Mac OS Compatibility	Mac OS 10.x
UNIX OS Compatibility	Sun OS4.1x; Solaris 2.x; AIX; HP-UX (LPR)
Interfaces	Standard: 10/100BaseTX, Hi-Speed USB 2.0, USB Host Interface
Network Print and Supported Protocols	TCP/IP, NetWare, AppleTalk, NetBEUI, IPsec, HTTPS, LDAP over SSL, SNMPv3, POP over SSL/SMTP over SSL
Drivers	KX Driver, Mini Driver, PPD for Mac, PPD for UNIX
Utilities	PRESCRIBE, KMnet Admin, KMnet Viewer, Status Monitor, PDF Direct Print, Command Center

### Scan Specifications

Scan Type	Color and Black & White Scanner
Scan Resolution	600dpi, 400dpi, 300dpi, 200dpi, 200 x 400dpi, 200 x 100dpi
Network Scan Speed	Mono: 300 dpi - 35 ipm Simplex; 18 ipm Duplex; 600 dpi - 20 ipm Simplex; 11 ipm Duplex Color: 300 dpi - 14 ipm Simplex; 8 ipm Duplex; 600 dpi - 7 ipm Simplex; 4 ipm Duplex
File Formats	TIFF, JPEG, XPS, PDF (Ver 1.4)
Connectivity / Supported Protocols	10/100BaseTX / TCP/IP; Hi-Speed USB 2.0
Scanning Functions	Scan to PC, Scan to e-mail, Scan to FTP, Scan to USB, WSD Scan
Driver	TWAIN Driver, WIA Driver

### Fax Specifications

Fax Type Compatibility	ITU-T Group3
Data Compression	MH / MR / MMR / JBIG
Fax Transmission Selection	Text, Photo, Text/Photo
Fax Memory	3.5 MB
Transmission Speed / Modem	3 Seconds or less per page / 33.6 kbps
Fax Memory Capacity	256 Sheets or more
Network Fax Reception	Supports SMB/FTP/e-mail protocols
Fax Functions	Duplex Transmission/Reception, One Touch Dial (22 numbers), FAX/TEL Switching, Sequential Broadcast (up to 100 parties), Quick Dial (100 numbers), Fax Reports

### USB Host Interface

Type	Supports direct printing and scanning from/to USB Drive
Supported File Types	Print: PDF, TIFF, XPS Scan: PDF (Ver 1.4), JPEG, TIFF, XPS

### Optional Paper Drawers

Paper Capacity	250 Sheets
Maximum Drawers	Up to two (2) PF-120 drawers can be added
Paper Size	Letter, Legal, A4, A5R, B5, Folio, Oficio 2, 5.8" x 8.3" - 8.5" x 14"
Paper Weight	16 - 32 lb Bond (60 - 120gsm)
Dimensions / Weight	14.8" W x 15.6" D x 3.9" H / 7.7 lbs

### Additional Options

Memory	Optional 256 MB, Optional 512 MB
--------	----------------------------------

Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).  
All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA  
©2011 Kyocera Mita America, Inc.

IC#

